

End Feed Fittings

Designed for end-feeding with soft solder or hard solder (brazing alloy). Ideal for use in hot and cold water services, central heating, fuel services and general engineering applications.

- WRAS approved
- Manufactured to BS EN 1354 Part 1



Working Temperature:
-40°C to +110°C



Maximum Working Pressure:
Up to 28mm
25 bar (-40°C to +65°C), 16 bar (+110°C)
35mm to 54mm
25 bar (-40°C to +30°C), 16 bar (+65°C)
10 bar (+110°C)

Couplings



Straight

0474	OD mm	£
M-EFSC-8	8	0.35
M-EFSC-10	10	0.35
M-EFSC-15	15	0.25
M-EFSC-22	22	0.50
M-EFSC-28	28	0.85
M-EFSC-35	35	2.60
M-EFSC-42	42	4.25
M-EFSC-54	54	6.00



Reducing Coupling

0474	OD mm	OD mm	£
M-EFRC-10-8	10	8	0.40
M-EFRC-15-10	15	10	0.45
M-EFRC-22-15	22	15	0.80
M-EFRC-28-15	28	15	1.35
M-EFRC-28-22	28	22	2.40

Tap Connectors



Straight

0474	OD mm	Thread	£
M-EFTCS-15-12	15	1/2"	0.90
M-EFTCS-15-34	15	3/4"	2.35
M-EFTCS-22-34	22	3/4"	1.70



Bent

0474	OD mm	Thread	£
M-EFTCB-15-12	15	1/2"	1.25
M-EFTCB-15-34	15	3/4"	6.10
M-EFTCB-22-34	22	3/4"	4.30

Crossovers



Full

0474	OD mm	£
M-EFCOF-15	15	2.05
M-EFCOF-22	22	4.10



Part

0474	OD mm	£
M-EFCOP-15	15	1.65
M-EFCOP-22	22	3.25

End Caps



End Caps

0474	OD mm	£
M-EFTC-8	8	0.40
M-EFTC-10	10	0.65
M-EFTC-15	15	0.45
M-EFTC-22	22	0.80
M-EFTC-28	28	1.65
M-EFTC-35	35	3.45
M-EFTC-42	42	4.90
M-EFTC-54	54	7.15