

Hi-Vis Air & Water RPVC Hose

The **Hi-Vis** properties of this hose are fully compliant with Health & Safety (Chromaticity Luminance) BS EN ISO 5774 and EN471:2003. A must for all professional facilities and applications.



Features:

- 20 bar rated
- -20°C to +80°C
- Suitable for potable drinking water
- Self-extinguishing
- High visibility
- Flexible PVC
- UV stable
- Multi-use
- White inner, yellow fluorescent outer
- Material softness BSS50/BSS65

Applications:

- Industrial
- Food
- Wash down
- Garage forecourt
- Workshops
- Vending
- Window cleaning/ high rise
- Festivals and outdoor public events



The components used in production of this hose are compliant with EC and FDA requirements

Applicable Standards BS EN ISO 5774 (plastic hoses, textile-reinforced types for compressed air applications.) Tested in accordance with EN471 : 2003 : Section 5.1,5.1.1 and Table 2 for both chromaticity and luminance.

Page Tech Sheet 10091

Hi-Vis Medium Duty, 30 Metre Coils

0349	ID mm	OD mm	mm	bar	£
HVIS06-30	6.3	11.5	28	20	65.20
HVIS08-30	8	13.5	34	20	79.80
HVIS10-30	10	16	40	20	104.40
HVIS12-30	12.5	18.5	55	20	115.20

Hi-Vis Medium Duty, 50 Metre Coils

0349	ID mm	OD mm	mm	bar	£
HVIS06-50	6.3	11.5	28	20	108.60
HVIS08-50	8	13.5	34	20	133.10
HVIS10-50	10	16	40	20	174.00
HVIS12-50	12.5	18.5	55	20	191.90

Hi-Vis Medium Duty, 100 Metre Coils

0349	ID mm	OD mm	mm	bar	£
HVIS06-100	6.3	11.5	28	20	217.15
HVIS08-100	8	13.5	34	20	266.10
HVIS10-100	10	16	40	20	347.95
HVIS12-100	12.5	18.5	55	20	383.85