

Translucent Silicone Tubing

Translucent silicone tube is non-toxic and biologically inert. It is FDA, BGA, WRC and NWC approved for drug and medical use, and meets European Pharmacopoeia class VI. Outstanding temperature resistance from -60°C to +200°C, it can withstand repeated autoclaving.

Excellent chemical resistance (contact technical department for advice).

Not suitable for high pressure applications.

Working Temperature:
-60°C to +200°C



10 Metre Coils

5012	ID mm	OD mm	mm	£
TST-04/020	2	4	1	28.40
TST-06/040	4	6	1	30.50
TST-08/050	5	8	1.5	44.50
TST-10/080	8	10	1	26.75
TST-12/080	8	12	2	65.90

FEP Tubing

Tech Sheet
20216



10 Metre Coils

5012	OD mm	£
4500400100	6	201.05
4500600100	8	238.70

PFA Tubing

Tech Sheet
60553



10 Metre Coils

5012	OD	£
4601000100	12mm	451.65
4600952159	1/2"	619.00

PTFE Tubing (Polytetrafluoroethylene)

The unique properties of PTFE are excellent. Enjoying a non-stick/low friction release property and a very wide temperature range, it is virtually inert to all known chemicals and solvents. It exhibits extremely good electrical insulation properties and good weatherability. All these characteristics combined make PTFE the ideal material for innumerable applications.

Please note: no recommended burst pressures/working pressures due to hose being unreinforced.

Tech Sheet
1379



10 Metre Coils

5012	ID mm	OD mm	mm	£
TPTFE-04/025-10M	2.5	4	0.75	87.30
TPTFE-06/040-10M	4	6	1	127.60
TPTFE-08/060-10M	6	8	1	178.60
TPTFE-10/080-10M	8	10	1	238.15
TPTFE-12/010-10M	10	12	1	273.85

30 Metre Coils

5012	ID mm	OD mm	mm	£
TPTFE-04/025-30M	2.5	4	0.75	261.95
TPTFE-06/040-30M	4	6	1	382.95
TPTFE-08/060-30M	6	8	1	535.65
TPTFE-10/080-30M	8	10	1	714.20
TPTFE-12/010-30M	10	12	1	821.20

LDP Low Density Polyethylene Tube



30 Metre Coils

5040	OD mm	ID mm	at 20°C psi	£
LDP04/025	4	2.5	200	20.85
LDP05/030	5	3	200	20.30
LDP06/040	6	4	185	31.65
LDP08/060	8	6	165	41.40
LDP10/080	10	8	150	46.55
LDP12/100	12	10	90	53.15

Customers who bought from this page also purchased...



Pneumatic Quick Release Series
21 Thermoplastic Couplings



...see pages 443-445