

316 Stainless Steel DIN 2353 Tube Fittings



EDELSTAHL / STAINLESS STEEL
VERBINDUNGSTECHNIK
FLUID CONNECTORS

Adjustable Elbows

Tech Sheet
10602



L Series, Metric,
Female Thread

0291



EWV-6L	6	M12 x 1.5	29.85
EWV-8L	8	M14 x 1.5	30.80
EWV-10L	10	M16 x 1.5	40.95
EWV-12L	12	M18 x 1.5	47.30
EWV-15L	15	M22 x 1.5	60.95
EWV-18L	18	M26 x 1.5	87.80
EWV-22L	22	M30 x 2	105.50
EWV-28L	28	M36 x 2	150.15
EWV-35L	35	M45 x 2	201.70
EWV-42L	42	M52 x 2	289.70

S Series, Metric,
Female Thread

0291



EWV-6S	6	M14 x 1.5	34.45
EWV-8S	8	M16 x 1.5	40.20
EWV-10S	10	M18 x 1.5	46.95
EWV-12S	12	M20 x 1.5	55.20
EWV-14S	14	M22 x 1.5	65.80
EWV-16S	16	M24 x 1.5	86.95
EWV-20S	20	M30 x 2	108.05
EWV-25S	25	M36 x 2	158.15
EWV-30S	30	M42 x 2	209.40
EWV-38S	38	M52 x 2	303.00

Straights

Tech Sheet
10605



L Series

0291



G6-UL	6	12.75
G8-UL	8	16.25
G10-UL	10	19.95
G12-UL	12	22.70
G15-UL	15	29.95
G18-UL	18	44.55
G22-UL	22	58.20
G28-UL	28	92.25
G35-UL	35	112.60
G42-UL	42	150.55

S Series

0291



G6-US	6	16.10
G8-US	8	18.95
G10-US	10	23.80
G12-US	12	26.70
G14-US	14	33.70
G16-US	16	44.45
G20-US	20	63.25
G25-US	25	105.35
G30-US	30	130.90
G38-US	38	175.75

Straight Reducers



Tech Sheet
10606

L Series

0291



GR-8L-6L	8	6	20.65
GR-10L-6L	10	6	22.30
GR-10L-8L	10	8	25.35
GR-12L-6L	12	6	25.55
GR-12L-8L	12	8	27.70
GR-12L-10L	12	10	29.65
GR-15L-6L	15	6	28.40
GR-15L-8L	15	8	30.50
GR-15L-10L	15	10	36.05
GR-15L-12L	15	12	37.30
GR-18L-8L	18	8	44.05
GR-18L-10L	18	10	50.80
GR-18L-12L	18	12	53.15
GR-18L-15L	18	15	55.80
GR-22L-8L	22	8	63.55
GR-22L-10L	22	10	63.55
GR-22L-12L	22	12	70.45
GR-22L-15L	22	15	69.70
GR-22L-18L	22	18	73.85
GR-28L-10L	28	10	99.05
GR-28L-12L	28	12	105.85
GR-28L-15L	28	15	102.70
GR-28L-18L	28	18	117.65
GR-28L-22L	28	22	121.70
GR-35L-15L	35	15	136.35
GR-35L-18L	35	18	136.50
GR-35L-22L	35	22	137.05
GR-35L-28L	35	28	148.90
GR-42L-15L	42	15	181.90
GR-42L-18L	42	18	181.90
GR-42L-22L	42	22	182.65
GR-42L-28L	42	28	183.30
GR-42L-35L	42	35	190.65



Stainless Steel 1.4571 Working Temperature:
-60°C to +400°C (DIN 17 440, AD W 10)

Seal Working Temperature:
-20°C to +200°C (FPM eg Viton)

Tech Sheet
10606

S Series

0291



GR-8S-6S	8	6	26.85
GR-10S-6S	10	6	30.45
GR-10S-8S	10	8	33.35
GR-12S-6S	12	6	35.10
GR-12S-8S	12	8	36.55
GR-12S-10S	12	10	36.50
GR-14S-6S	14	6	36.15
GR-14S-8S	14	8	36.35
GR-14S-10S	14	10	40.20
GR-14S-12S	14	12	44.30
GR-16S-6S	16	6	47.30
GR-16S-8S	16	8	47.50
GR-16S-10S	16	10	46.75
GR-16S-12S	16	12	52.45
GR-16S-14S	16	14	59.95
GR-20S-6S	20	6	62.75
GR-20S-8S	20	8	62.75
GR-20S-10S	20	10	69.45
GR-20S-12S	20	12	73.15
GR-20S-14S	20	14	71.80
GR-20S-16S	20	16	82.75
GR-25S-8S	25	8	117.20
GR-25S-10S	25	10	117.20
GR-25S-12S	25	12	117.20
GR-25S-14S	25	14	117.35
GR-25S-16S	25	16	129.80
GR-25S-20S	25	20	172.85
GR-30S-10S	30	10	163.55
GR-30S-12S	30	12	163.55
GR-30S-14S	30	14	163.55
GR-30S-16S	30	16	164.30
GR-30S-20S	30	20	165.05
GR-30S-25S	30	25	175.75
GR-38S-10S	38	10	210.50
GR-38S-12S	38	12	210.50
GR-38S-14S	38	14	210.50
GR-38S-16S	38	16	216.20
GR-38S-20S	38	20	212.65
GR-38S-25S	38	25	216.30
GR-38S-30S	38	30	216.30

2-3 day delivery service from manufacturer, if not available from stock