Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep., Media, Monitor & Test

KELM™ Pneumatics Pneumatic & Vacuum Equipment

Valves

Adaptors & Fittings

Stainless Steel Malleable

Modular Coolant Hose System



Page Tech Sheet 68071

Compatibility:

Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.

Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Features:

- Unique ball and socket design, fully handadjustable in both position and length
- Will not kink or fatigue; bending does not decrease the inside diameter

Material: polyoxymethylene (POM).
Recommended Maximum Line Pressure:

Recommended Maximum Flow Rate: 1,800 litres per hour.
Interchangeable with: Loc-Line.

- Will not damage machine tool cutters if contact occurs, unlike metal hoses
- Electrically non-conductive; ideal for EDM flushing
- No internal positioning rod that can break or restrict fluid flow



Repeated exposure to this temperature will cause fatigue.

- · Stays in position; repeated positioning is easy
- · Creep due to machine vibration is eliminated

1/4" Series



Round Nozzles

0518	Nozzle Hole Size	3
28015	1/16"	1.75
28016	1/8"	1.75
28017	1/4"	1.75



90° Round Nozzles

0518	Nozzle Hole Size	3
28019	1/16"	1.75
28020	1/8"	1.75
28021	1/4"	1.75



90° Spray Bar Nozzle

0518	Nozzle Hole Size	£
28022	Size 60	2.20





Size 60



Flare Nozzle

28027

0518	Nozzle Hole Size	£
28028	1"	1.75



Swivel Nozzle

1.75

0518	Nozzie Hole Size	3
28029	Size 40	13.45



Male Connectors, NPT

1.75
1.75

Clamps & Clips Sprays & Adhesives Blow Guns, Vacuum & Nozzles

Hose, Tubing & Couplings

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

> oois, Hardware k PPE

