


# Modular Coolant Hose System



## Page Tech Sheet68071

Compatibility:  
Suitable for use with acetone, alcohol, ethyl, greases, oils, commercial dish detergents, gasoline, lacquer solvents and sodium hydroxide.  
Not for use with chlorine, acids, ammonium hydroxide, bases (strong), hypochlorite ion solutions or sodium hypochlorite.

Material: polyoxymethylene (POM).  
Recommended Maximum Line Pressure: 30 psi  
Recommended Maximum Flow Rate: 2,150 litres per hour.  
Interchangeable with: Loc-Line.

 Maximum Operating Temperature: +76°C  
Repeated exposure to this temperature will cause fatigue.

### 1/2" Series



#### Round Nozzles

| 0518  | Nozzle Hole Size | £    |
|-------|------------------|------|
| 48013 | 1/16"            | 2.20 |
| 48014 | 1/8"             | 2.20 |
| 48015 | 1/4"             | 2.20 |



#### Flat Nozzle

| 0518  | Nozzle Hole Size | £    |
|-------|------------------|------|
| 48024 | Size 80          | 3.30 |



#### Flare Nozzles

| 0518  | Nozzle Hole Size | £    |
|-------|------------------|------|
| 48026 | 1.1/4"           | 4.35 |
| 48027 | 2.1/2"           | 4.35 |



#### Flat Holed Nozzles

| 0518  | Nozzle  | £    |
|-------|---------|------|
| 48022 | 5 Holes | 3.30 |
| 48023 | 7 Holes | 3.30 |



#### Male Connectors, NPT

| 0518  |      | £    |
|-------|------|------|
| 48030 | 3/8" | 2.20 |
| 48031 | 1/2" | 2.20 |



#### Y Connector

| 0518  | £    |
|-------|------|
| 48032 | 3.30 |



#### 90° Elbow Connector

| 0518  | £    |
|-------|------|
| 48034 | 3.30 |

For...



Reinforced PVC  
Braided Hose



...see page 1320