

Copper Tubing & Accessories

Polyethylene Pipe Insulation

Thermal Conductivity DIN 52613:
0.035W(m.K) at 0°C.

Fire Rating BS479 Part 5:1979:

Class P (not easily ignitable).

High Quality CFC Easy-Fit closed cell pipe insulation. Particularly effective for the thermal insulation of domestic heating and plumbing pipe work for energy conservation and frost protection. Easy to install, none fibrous and creates no dust during installation and is resistant to oils and greases.



Working Temperature:
-50°C to +100°C



9mm Wall Insulation (Semi Split), 2 Metre Lengths

5070	ID. mm	£
POLY15X9	15	5.10
POLY22X9	22	6.60
POLY28X9	28	7.85

13mm Wall Insulation (Semi Split), 2 Metre Lengths

5070	ID. mm	£
POLY15X13	15	5.90
POLY22X13	22	7.65
POLY28X13	28	10.30

19mm Wall Insulation (Split through 1 Wall Thickness), 2 Metre Lengths

5070	ID. mm	£
POLY15X19	15	13.00
POLY22X19	22	16.25
POLY28X19	28	19.00

25mm Wall Insulation (Split through 1 Wall Thickness), 2 Metre Lengths

5070	ID. mm	£
POLY15X25	15	22.50
POLY22X25	22	22.65
POLY28X25	28	30.00

Copper Tube Reamer



Internal/External Reamer for Tube

5070	To Suit O.D. mm	£
CTR1	3-36	34.60

Automatic Tube Cutters

- Single action automatic tube cutting in tight locations.



5100	OD mm	£
88801	15	47.85
88802	22	50.45
88804	21 3/4" Irish	50.45

Copper Tube Cutters



Standard Cutter

5100	To Suit O.D. mm	£
CTC1	3-28	14.65



Mini Cutter

5100	To Suit O.D. mm	£
CTC2	3-16	12.75

For...

Fire Extinguishers



...see page 1807