

Lightweight PVC Ducting

CP PVC 465



Flexible suction and blast hose, PVC-coated reinforced fabric wall with supporting galvanised steel spiral.

Applications: for air conditioning/ventilation, extraction arms and welding fume extraction.

- Flame retardant
- Good resistance to chemicals, acids and alkalis
- Highly flexible and lightweight
- External abrasion protection provided by spiral
- Patented 'clamp profile' design

Use clamp type 212 (refer to page 1413).

Working Temperature:
-10°C to +80°C
Intermittent to:
+110°C



PROTAPE PVC 310, GREY

Premium quality lightweight ducting made from high-grade flexible PVC with spring steel reinforcement integrated into the wall.


Applications: for extracting dust, powders, fumes and gases. Also for air conditioning and ventilation applications.

Wall Thickness: 0.6mm approx.

- Phthalates free
- Wire spiral reinforcement can be earthed
- Highly flexible and lightweight
- Small bend radius, kink proof
- Good resistance to chemicals, acids and alkalis
- UV and ozone resistant

Use clamp type 208/212 (refer to page 1413).

Working Temperature:
-20°C to +70°C
Intermittent to: +80°C



Tech Sheet
10422

Tech Sheet
10408

Lightweight, Clamp Profile, Suction & Blower, 3 Metres

0392	ID mm	OD mm	bar	Vacuum bar	kg per m ²	£
465-0050-0000	50	62	0.570	0.340	0.440	51.10
465-0065-0000	65	77	0.410	0.230	0.540	65.35
465-0075-0000	75	87	0.380	0.180	0.630	73.45
465-0100-0000	100	112	0.210	0.100	0.540	94.65
465-0125-0000	125	137	0.185	0.070	0.660	128.15
465-0150-0000	150	162	0.140	0.040	0.790	147.60
465-0160-0000	160	172	0.135	0.035	0.830	151.75
465-0200-0000	200	212	0.105	0.025	0.800	189.15
465-0225-0000	225	237	0.095	0.020	0.880	219.40
465-0250-0000	250	262	0.075	0.020	0.980	231.85

Light Duty PVC Ducting, 10 Metres

0392	ID mm	OD mm	bar	Vacuum bar	kg per m ²	£
310-0032-0000	32	39	0.875	0.200	0.260	147.35
310-0038-0000	38	45	0.740	0.185	0.300	147.35
310-0050-0000	50	58	0.410	0.155	0.310	164.55
310-0055-0000	55	63	0.370	0.140	0.330	148.55
310-0065-0000	65	73	0.315	0.105	0.390	161.70
310-0075-0000	75	83	0.275	0.085	0.450	170.85
310-0080-0000	80	88	0.255	0.075	0.470	207.00
310-0090-0000	90	98	0.230	0.065	0.530	185.20
310-0100-0000	100	108	0.205	0.050	0.570	192.65
310-0125-0000	125	133	0.165	0.035	0.710	238.50
310-0150-0000	150	158	0.135	0.035	0.840	281.50
310-0160-0000	160	168	0.130	0.030	0.870	341.75
310-0200-0000	200	208	0.105	0.025	1.110	847.30

PROTAPE PVC 371

Tech Sheet
10407

Super Lightweight, Suction & Blower, 10 Metres

0392	ID mm	OD mm	bar	Vacuum bar	kg per m ²	£
371-0051-0000	51	54	0.240	0.145	0.120	152.50
371-0060-0000	60	63	0.200	0.110	0.140	158.25
371-0076-0000	76	79	0.160	0.080	0.180	171.45
371-0080-0000	80	83	0.150	0.080	0.190	174.30
371-0102-0000	102	105	0.120	0.050	0.240	186.90
371-0127-0000	127	130	0.095	0.035	0.320	231.05
371-0152-0000	152	155	0.080	0.035	0.370	271.75
371-0160-0000	160	163	0.075	0.025	0.440	287.80
371-0203-0000	203	206	0.060	0.020	0.600	373.75
371-0254-0000	254	258	0.045	0.015	0.790	485.55
371-0305-0000	305	309	0.040	0.010	0.950	587.00


Super-lightweight ducting made from fabric reinforced flexible PVC tape with spring steel reinforcement integrated into the wall.

Applications: for air conditioning/ventilation, extraction arms and welding fume extraction.

- Flame retardant
- Wire spiral reinforcement can be earthed
- Highly flexible and lightweight
- Shipped compressed to save space
- Good resistance to chemicals, acids and alkalis

Use clamp type 208, 212 (refer to page 1413).

Working Temperature:
-10°C to +80°C
Intermittent to:
+110°C



Other size & length options are available for all hoses shown here - please enquire