

Mountable Stainless Steel Hose Reels

- All stainless steel 304 spring rewind hose reels are designed for harsh, corrosive environments or where hygiene is of primary importance
- Ideally suited for wash down applications in food processing, also for marine and offshore application

- All stainless steel swivel assemblies with PTFE washer and viton o-ring for high pressure and high temperature
- Spring fully enclosed and lubricated

- Guide arm adjustable for handling up to 6 positions
- Multi-position ratchet lock keeps hose at desired length

Other configurations available on request.

Tech Sheet
67921

STAINLESS
STEEL



Spring Rewind Without Hose, 3/8"

0800	To Suit	Capacity	£
SSHR-15N-38	3/8" BSP Outlet	15m	890.70

- Maximum Working Temperature: +155°C
- Maximum Working Pressure: 175 bar

Tech Sheet
67922

STAINLESS
STEEL



Blue 1 Wire Pressure Wash, Spring Rewind, 3/8"

0800	Female	L mtrs	£
SSHR-15-38SB106F	3/8" BSP	15	1086.55

- Working Temperature: -20°C to +80°C
- Maximum Working Pressure: 20 bar

Tech Sheet
67923

STAINLESS
STEEL



Hi-Vis Air & Water, Spring Rewind, 3/8"

0800	Male	L mtrs	£
SSHR-15-38SHV06T	3/8" BSPT	15	923.55
SSHR-15-38SHV08T	1/2" BSPT	15	923.55

- Maximum Working Temperature: +100°C
- Maximum Working Pressure: 10 bar

Tech Sheet
67924

STAINLESS
STEEL



Non Marking Wash Down Hose, Spring Rewind, 1/2"

0800	Male	L mtrs	£
SSHR-15-12SWD08T	1/2" BSPT	15	1142.60