

Retracta Standard Hose Reels

Redashe Retracta spring rewind hose reels offer performance, reliability and versatility for all popular hose applications. Constructed in high impact UV stabilized polypropylene for all-purpose corrosion free, durability. Retracta reels can be installed indoors or out. They are particularly suited to washdown applications in food processing as an alternative to conventional stainless steel reels. Suitable for wall, floor, bench or overhead installations.

Features:

- Superior positive latching mechanism allows the reel to be mounted in any position, with latching of the hose at any length
- Tough, corrosion free polypropylene construction
- Lightweight-average just 12kg, easy to install
- Fully automatic hose rewind for neat and tidy storage
- Low rewind tension allows for easy hose "pull out"
- Virtually maintenance free
- Completely serviceable-all parts readily available
- 5 year warranty (conditions apply)
- Safe storage system that keeps hoses off the floor



Excluding hose.

NOTE: available for many other applications, with or without hose.
Hose: reinforced PVC.

Retracta Compressed Air Hose Reels

0122	L mtrs	ID mm	Inlet BSPP	Outlet BSPT	Bar	Color	£
AR100	20	10	3/8" Female	1/4" Male	16	Red	510.70
AR200	15	12.5	3/8" Female	3/8" Female	16	Red	540.35

Hose: reinforced PVC.

Retracta Cold Wash Reel, 40°C

0122	L mtrs	ID mm	Outlet BSPT	Bar	Color	£
CW100	15	12.5	Bare End	10	Blue	612.50

Hose: reinforced rubber.

Retracta Hot Wash Reel, 90°C

0122	L mtrs	ID mm	Inlet BSPP	Outlet BSPT	Bar	Color	£
HW100	12	12.5	3/8" Female	3/8" Male	10	Red	693.90

Hose: reinforced rubber.

Retracta Food Quality Water Reel, 95°C

0122	L mtrs	ID mm	Inlet BSPP	Outlet BSPT	Bar	Color	£
FQ100	12	12.5	3/8" Female	1/2" Male	20	Red	732.70

Retracta Garden Reel

0122	L mtrs	ID mm	Inlet BSPP	Outlet BSPT	Bar	Color	£
DR100	18	12.5	3/4" Male	Blank/Nozzle	7	Green	451.50

Retracta Breathing Air Reels (EN139)

0122	L mtrs	ID mm	Inlet BSPP	Outlet BSPT	Bar	Color	£
BH100	15	10	3/8" Female	3/8" Male	12	Red	758.65

Heavy Duty Spring Rewind Hose Reels



Redashe heavy duty hose reels are engineered for rugged durability. Constructed in heavy gauge powder coated steel for maximum strength and reliability, these spring rewind reels provide years of trouble free service with minimum maintenance. The eight-position roller arm adjusts for wall, overhead and floor mounting while the full flow swivel ensures maximum product delivery.


All models available with or without fitted hose.

NB: hose not supplied.
Model shown: SHL-N-550.

Features:

- Heavy duty steel construction with durable blue powder finish
- Double supported solid 1" steel axle
- Multi position roller arm gives full range of mounting positions
- Four direction non-sag roller guides reduce hose wear
- 1/4" steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Latching of hose at any length
- All 15 metre (50') capacity; SHL-N-575 22.6 metre capacity

Maximum Working Pressure for Reel: 300 psi



Suitable for Air, Water, Food, Industry & Diesel, without Hose

0122	Female	L mtrs	£
P-LPL-350	3/8" BSPP	15	594.95
SHL-N-450	1/2" BSPP	15	714.35
SHL-N-550	3/4" BSPP	15	1193.35
SHL-N-575	3/4" BSPP	22.6	1407.20
SHL-N-650	1" NPT	15	1407.20

Heavy Duty, High Pressure Spring Rewind Hose Reels



Designed for high pressure delivery of water, oil and grease. The oil and grease models are ideally suited to lubrication systems in automotive workshops where durability and reliability are paramount. For pressure washer users the 3000 psi/+150°C rating of the medium pressure water reels provides a solution to the problem of persistent hose damage.

Features:

- Heavy duty steel construction with durable blue powder finish
- Double supported solid 1" steel axle
- Multi position roller arm gives full range of mounting positions
- Four direction non-sag roller guides reduce hose wear
- 1/4" steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Latching of hose at any length
- Fully automatic hose rewind for neat and tidy storage
- Externally mounted full flow swivel for maximum product delivery
- All 15 metre (50') capacity

NB: hose not supplied.

Maximum Working Pressure for Reel: 3000 psi



Suitable for Water, Steam, Oil & Grease, without Hose

0122	Female	£
MPL-N-350	3/8" BSPP	749.95