

Hose Reels

EZ-Coil Safety Reels

The EZ-Coil™ Rewind Safety System is a patented rotary-dampening system. The EZ-Coil™ Rewind Safety System controls and eliminates the high-speed recoil motion associated with conventional spring driven hose reels with no increase in the amount of resistance when pulling out the hose.

LOW PRESSURE COXREELS – can be used for multiple applications such as air, water, oil, diesel, breathing air, etc. Supplied as standard without hose, covering pressures up to 300 psi (20 bar) and temperatures up to +121°C.

MEDIUM PRESSURE COXREELS – can be used for multiple applications such as oil, jetting, air and water. Working pressures up to 3,000 psi (200 bar) and temperatures up to +121°C.

Safety Series Features:

- Up to 80% slower retraction
- Equipped with the EZ-Coil™ rewind safety system
- No electricity required
- Pull-out tension remains unaffected
- Powder painted blue
- Smooth rolled edges on the side discs

COXREELS Standard Features:

- Heavy duty construction, made in the USA
- Available in low, medium and high pressure
- Heavy duty 1/4" plate steel support post and mounting plate
- 1" oil-lite self-lubricating bearing
- Solid 1" steel centre support shaft
- Full flow swivel joint
- Adjustable arm guide wall, floor, ceiling and pit mountable
- Eight position locking ratchet
- Four roller no-snap hose guide



2 YEAR WARRANTY

Low Pressure

0122	L mtrs	ID	PSI	£	
EZ-P-LPL-350	15	3/8"	3/8"	300	683.20
EZ-SHL-N-450	15	1/2"	1/2"	300	807.65
EZ-SHL-N-4100	30	1/2"	1/2"	300	1233.00
EZ-SHL-N-550	15	3/4"	3/4"	300	1224.55

Medium Pressure

0122	L mtrs	ID	PSI	£	
EZ-MPL-N-350	15	3/8"	3/8"	3000	870.10
EZ-MPL-N-450	15	1/2"	1/2"	3000	909.05

Spring Rewind Cable Reel, 110V

Features:

- Heavy gauge, all steel construction
- Durable yellow powder-coated finish
- Automatic rewind easily wraps, stores and protects electrical cable
- Heavy gauge steel base and support post
- Factory matched cartridge style spring motor
- 1" solid steel axle with 1" lubricated precision bearing
- Guide arm adjusts to wall, floor and overhead positions
- Four-way roller guide to reduce cable wear
- Multi-position lock ratchet secures cable at desired working length
- Non-corrosive stainless steel latch spring, pawl and zinc-plated ratchet
- Supplied complete with 15m yellow artic-grade (-40°C) PVC cable plus 1m connecting cable and yellow, 3 core, 110V 16A plug and socket



2 YEAR WARRANTY

Spring Rewind Cable Reel, 110V

0122	⚡	L mtrs	£
SPC13-110V	110V	15	792.65

ABS Spring Rewind Cable Reel

Construction from ABS gives a smooth finish, higher strength, rigidity, durability and chemical resistance. Supplied complete with 20m x 3 core x 1.5mm² fitted hose and is suitable for use in industrial and workshop applications with small power tools and other electrical appliances. The reel is supplied as standard with a pivoting wall bracket.

Features:

- Constructed in ABS plastic
- Latching of cable at any length
- Fully automatic spring rewind
- Low effort easy to use rewind tension
- Supplied with fitted cable
- Virtually maintenance free
- Supplied complete with integral wall mounting swivel bracket



1 YEAR WARRANTY

ABS Spring Rewind Cable Reel

0122	⚡	L mtrs	£
CPER-120	240V	20	279.75

3 Phase Cable Reel

The Redashe 6888 Series is a high performance spring rewind cable reel, constructed in powder-coated steel. It is supplied complete with 15m x 5 core, 2.5mm² cable and a 2m lead-in cable.

Overload protection is provided by a circuit breaker built into the rear housing.

Plug and sockets not supplied.

Features:

- Non-snap roller guides to reduce cable wear
- Latching of cable at any length
- Corrosion resistant powder coated finish
- Suitable for floor, wall, ceiling or vehicle mount
- Fully automatic cable rewind for neat and tidy storage
- Multi-position roller guide assembly
- Externally mounted fully enclosed and lubricated spring assembly
- CE marked



1 YEAR WARRANTY

6888 Series

0122	L mtrs	Rolled Watt	Extended Watt	⚡	£
C6888-380V-50	15	5000	7200	380V	612.10

Static Discharge Reel

Redashe SD reels provide convenient storage of static grounding cable with fast payout and automatic spring rewind. Designed for safe and reliable grounding of vehicles, aircraft and other equipment requiring static bonding.

Features:

- Heavy duty construction
- Fully automatic spring rewind
- Non-sparking latching mechanism
- 4mm galvanized steel cable with high-visibility orange vinyl cover
- 50 amp grounding clamp
- Multi-position rewind guide arm
- 1" solid steel axle
- Durable blue powder coat finish
- Cartridge style spring motor
- Zinc-plated current path



1 YEAR WARRANTY

Spring Rewind

0122	L mtrs	OD mm	Max Resistance ohm	£
SD-50	15	4	1.3	494.95
SD-100	30	4	2.6	690.25