

Hose Reels

Redashe

ABS Spring Rewind Hose Reel

Construction from ABS gives higher impact strength, rigidity, durability and chemical resistance. Suitable for use in industrial and workshop applications. The reel is supplied as standard with a fitted hose and a pivoted wall bracket.

Features:

- Constructed in ABS plastic
- Latching of hose any length
- Fully automatic spring rewind
- Low effort easy to use rewind tension
- Supplied with fitted hose
- Virtually maintenance free
- Supplied complete with integral wall mounting swivel bracket



ABS Spring Rewind Hose Reel

0122					
CPAR-1120	20	3/8"	3/8"	145	304.50

Slow Motion Safety Reels

The compact spring rewind reel operates with a normal retraction system but should the operator lose grip on the hose, then the system senses the over-speed reaction and slows the hose to a safe speed by means of a centrifugal brake.

Features:

- Constructed in high impact UV stabilised polypropylene
- Powder coated, integral wall/ceiling bracket
- Latching of cable at any length or free run option
- Fully automatic spring rewind
- Low effort easy to use rewind tension
- Lightweight design
- Supplied with fitted hose
- Virtually maintenance free
- 12 month manufacturer's warranty



Slow Motion Safety Reels

0122					
RA250SM	15	8	1/4"	150	381.75
RA300SM	10	10	3/8"	150	426.45

E-Zy Reels

Features:

- Lightweight and durable, just 12.5kg
- Constructed in high-impact UV-stabilised polypropylene
- Supplied with correct type of hose for specific application
- Fully assembled, includes 3 connecting hose

- Suitable for air or water depending on model



E-Zy Reel 701/705, Air/Water, BSPT

0122					
C705-100	10	1/4"	1/4"	12	141.60
C705-200	8	5/16"	1/4"	12	148.90
C701-100	15	3/8"	3/8"	20	207.00
C701-200	15	1/2"	1/2"	20	241.85

E-Zy Reel 701, Garden

0122					
C701-GAR	20	12.5	10	Green	136.20

808 Welding Series are a high performance spring rewind hose reels, constructed in black powder-coated steel. Reels are supplied as standard without hose, but have capacities of either 50 x 3/8" twin or 65 x 1/4" twin gas hoses. Suitable for either wall, floor or ceiling mount.

Features:

- Full flow, brass swivel assembly ensures maximum product delivery
- Double O-ring design to prevent leakage
- Latching of hose at any length
- Positive latching action
- Four-way roller guides to prevent hose wear
- Multi-position guide arm to suit most mounting positions

- Sold as a bare reel, hose at extra cost



E-Zy Reel 808, Welding, BSPT

0122				
C808-165W	20	1/4"	3/8"	514.75
C808-350W	15	3/8"	3/8"	542.90

Features:

- Compact, lightweight design
- Fully automatic spring rewind
- Supplied with 15m of 3 core, 1.5mm cable
- Low effort, easy to use rewind tension
- Fitted inlet cable for connection to supply
- Virtually maintenance free

- Integral wall mounting swivel bracket
- 240V
- Latching of cable at any length



Electrical Cable Reel

0122	
C605-100	118.05

Compact Stainless Steel Hose Reels

- Constructed in heavy gauge 304 grade stainless steel
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Externally mounted spring canister
- Floor and wall mounting options

- Compact design
- Supplied as bare reel, hose available at extra cost



Maximum Working Pressure for Reel: 300 psi (20 bar)

CTWA Stainless Steel Compact, Hose Reel Only

0122					
CTWA-1315SS	1/2"	7/8"	15	300	803.95

Introducing the new stainless steel, high capacity, spring rewind, hose reel. Constructed in heavy-gauge 304 grade stainless steel which offers strength, performance and reliability, along with a professional a modern look.

- 304 grade stainless steel
- Rolled and ribbed side discs for strength and rigidity
- Four-way roller guide to reduce hose wear
- Swept riser assembly for easy hose installation
- Fitted with Viton seals as

standard, swivel has a twin O-ring design for extended trouble-free service

- Externally mounted spring canister and swivel assembly for easy maintenance



Stainless Steel Spring Rewind Reel, Hose Reel Only

0122					
CCRHA-1320SS	1/2"	7/8"	20	2500	1257.10
CCRHA-1330SS	1/2"	7/8"	30	2500	1300.90
CCRHA-1920SS	3/4"	1.1/8"	20	1500	1332.85
CCRHA-1930SS	3/4"	1.1/8"	30	1500	1443.55
CCRHA-2520SS	1"	1.1/2"	20	1200	1416.30

- Heavy-gauge 304 grade stainless steel
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Floor and wall mounting options

- Smooth and positive crank design
- Supplied as bare reel, hose available at extra cost



Maximum Working Pressure for Reel: 700 psi (48 bar)

CRWM-SS Stainless Steel, Manual Rewind Series, High Capacity, Hose Reel Only

0122					
CRWM-1920SS	3/4"	1.1/8"	20	700	1080.40
CRWM-2520SS	1"	1.1/2"	20	700	1235.45