

Hose Reels

Redashe

Stainless Steel, Portable Hose Reels

Swivel in/out:
1/2" female x 1/2" female
Width: 622mm
Depth: 680mm
Height: 1100mm

- 304 stainless steel construction
- Full flow swivel assembly for maximum product delivery
- Stainless steel swivel shaft, nickel-plated milled brass body
- Fitted with Viton seals as standard. Swivel has a twin O-ring design for extended trouble-free service
- Swept riser assembly for easy hose installation

- Smooth and positive direct crank design
- Ideally suited for wash down applications in the food industry, chemical manufacturing, marine and offshore installations
- Anti-slip rubber feet to prevent movement when extending hose
- Supplied as a bare reel, hose to suit application at extra cost



2 YEAR WARRANTY

Hose Reel Only

0122	ID	OD	L mtrs	PSI	£
CCPOR-1345SS	1/2"	7/8"	45	700	1125.90
CCPOR-1930SS	3/4"	1.1/8"	30	700	1350.90

Stainless Steel, Manual Side Mount Hose Reel

The CCMHR-1320 stainless steel manual reel offers a hose storage solution for harsh, corrosive environments or where hygiene is of primary importance. The unit is ideally suited for food processing, marine and offshore applications. Initially designed for marina installations to convey drinking water and other media.

- Constructed in 316 stainless steel
- Direct manual rewind

- 360° payout and retrieval directions
- Rolled side discs for additional strength
- Swept riser assembly for easy hose installation
- Pedestal side mount only
- Compact and lightweight design
- Supplied as a bare reel, hose to suit application at extra cost



Maximum Working Pressure:
300 psi (20 bar)

2 YEAR WARRANTY

Hose Reel Only

0122	ID	OD	L mtrs	PSI	£
CCMHR-1320SS	1/2"	7/8"	20	300	1183.30




A Brand New Concept in Hose Reel Technology

FEATURES & BENEFITS OF THE CONCEPT:

- Eliminates the use of a fixed guide arm in a wall/ceiling mount position
- Easy to install with no need for post installation adjustments
- Unique, automatic, 90° vertical rotational span
- Covers various mounting positions
- Balanced clock spring produces enough torque to displace the weight of the guide arm
- Allowing the guide arm to move vertically up and down in a smooth, effortless and fully automatic manner
- The roller guide and arm/s will always be directly facing the user, giving total control on payout and retrieval
- Allows the units to be mounted at an increased height
- Removes the possibility of harm to the operator, passing personnel or damage to machinery compared to low-level units
- Roller guide arm returns to its rest position after use
- Sets the reel ready for the next operator

STANDARD FEATURES:

- Constructed in heavy gauge powder coated steel
- Finished in a durable, white powder coated gloss finish
- Latching of hose at any length
- Fully automatic hose rewind for neat, tidy storage
- Extended roller guide aperture to ease hose stacking
- Externally mounted swivel assemblies
- Viton seals and nylon backup rings as standard
- Low, medium and high pressure applications
- Double supported 1", solid steel axle
- Pathfinder® self-adjusting roller guide arm
- All working parts fully accessible for servicing
- Floor, wall or ceiling mounting options
- Suitable for air, water, oil, diesel and grease delivery
- 2-year manufacturer's warranty
- Swivels 180° through the X axis and 90° through the Y axis
- Supplied as a bare reel, hose to suit application at extra cost



Low Pressure, Hose Reel Only

0122	ID	L mtrs	PSI	£
PFS-915L	3/8"	15	300	715.40
PFS-920L	3/8"	20	300	744.50
PFS-1315L	1/2"	15	300	753.55
PFS-1320L	1/2"	20	300	771.75

Medium Pressure, Hose Reel Only

0122	ID	L mtrs	PSI	£
PFS-915M	3/8"	15	2250	744.50
PFS-920M	3/8"	20	2250	784.40
PFS-1315M	1/2"	15	2000	780.80
PFS-1320M	1/2"	20	2000	849.90

High Pressure, Hose Reel Only

0122	ID	L mtrs	PSI	£
PFS-615H	1/4"	15	5000	762.75
PFS-915H	3/8"	15	4000	780.80



HYDRAQUIP
HOSE & HYDRAULICS

www.hydraquip.co.uk