

Hose Reels

Redashe

12.3 Hose Reels

High Capacity, High Visibility Rewind Hose Reels

- Constructed in heavy gauge mild steel
- Highly visible yellow powder coated finish
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Externally mounted spring canister and swivel assembly for easy maintenance
- Floor and wall mounting options
- Capacities up to 30m
- Two-year manufacturer's warranty
- Supplied as bare reel, hose available at extra cost



Maximum Working Pressure for Reel:
Up to 2700 psi (186 bar)



CRHA Spring Rewind, Air, Oil, Water & Diesel

0122	ID	OD	L mtrs	PSI	£
CRHA-920	3/8"	5/8"	20	2700	719.05
CRHA-930	3/8"	5/8"	30	2700	779.05
CRHA-1320	1/2"	7/8"	20	2500	760.10
CRHA-1920	3/4"	1.1/8"	20	1500	818.90
CRHA-1930	3/4"	1.1/8"	30	1500	918.75
CRHA-2520	1"	1.1/2"	20	1200	989.65

The high capacity CCRHA-940M spring rewind hose reel offers all the strength and reliability that you would expect of the RHA series. Designed to carry 40m of jetting hose at 3,000 psi/205 bar, for applications where a longer length of hose is needed on a spring rewind unit.

- Twin pedestal supports
- Heavy gauge, all steel construction
- Durable blue powder-coated finish
- Full flow swivel assembly for

maximum product delivery

- Swept riser assembly for easy hose installation
- Fitted with Viton seals as standard.
- 40m hose capacity
- Externally mounted spring canister and swivel assembly for easy maintenance
- Rolled and ribbed side discs for strength and rigidity
- Four-way roller guide to reduce hose wear
- Floor or wall mounting options



Spring Rewind Reels, Hose Reel Only

0122	ID	OD	L mtrs	PSI	£
CCRHA-940M	3/8"	5/8"	40	3000	1035.00

Introducing the new high visibility, high capacity series welding reels. Constructed in heavy gauge powder-coated steel, offering strength, performance and reliability. Capacities of 20m and 30m for either oxy-acetylene or oxy-propane gas applications.

- Twin pedestal supports
- Heavy gauge, all steel construction
- Durable, yellow powder-coated finish
- Full flow swivel assemblies for maximum product delivery



Spring Rewind Welding Reels, Hose Reel Only

0122	ID	OD	L mtrs	PSI	£
CCRG-820	3/8"	5/8"	20	200	735.40
CCRG-830	3/8"	5/8"	30	200	793.50

Introducing the new high visibility, high capacity series welding reels. Constructed in heavy gauge powder-coated steel, offering strength, performance and reliability. Capacity of 20m for either oxy-acetylene or oxy-propane gas applications.

- Twin pedestal supports
- Heavy gauge, all steel construction
- Durable, yellow powder-coated finish
- Full flow swivel assemblies for maximum product delivery




Maximum Working Pressure for Reel:
200 psi (14 bar)



Manual Rewind Welding Reel, Hose Reel Only

0122	ID	OD	L mtrs	PSI	£
CCRGM-820	3/8"	5/8"	20	200	630.15

- Swept riser assembly for easy hose installation
- Fitted with Viton seals as standard
- Large four-way roller guide to reduce hose wear
- Externally mounted spring canister and swivel assemblies for easy maintenance
- Supplied as a bare reel, hose to suit application at extra cost



- Constructed in heavy gauge mild steel
- Highly visible yellow powder-coated finish
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear



Maximum Working Pressure for Reel:
700 psi (48 bar)



CRWM Manual Rewind, Air, Oil, Water & Diesel

0122	ID	OD	L mtrs	PSI	£
CRWM-1320	1/2"	7/8"	20	700	572.00
CRWM-1340	1/2"	7/8"	40	700	630.15
CRWM-1920	3/4"	1.1/8"	20	700	712.60
CRWM-1940	3/4"	1.1/8"	40	700	795.35
CRWM-2520	1"	1.1/2"	20	700	769.95
CRWM-2530	1"	1.1/2"	30	700	818.90

You might also need...

KELMK
Enhanced Quality Performance

Safety Air Blow Guns



...on page 1598