

Manual Rewind Welding Reel, Hose Reel Only

Redashe

High Visibility Portable Hose Reels

Swivel in/out:
1/2" female x 1/2" female
Width: 512mm
Depth: 380mm
Height: 445mm

- Heavy gauge, all steel construction
- Highly visible yellow powder-coated finish
- Pressed and ribbed side discs for strength and rigidity
- Stainless steel internal plumbing and swivel shaft

- Fitted with Viton seals as standard
- Direct hand crank design
- Detachable crank handle
- Ideal for agriculture, construction and industrial applications
- Supplied as a bare reel, hose to suit application at extra cost
- Lightweight, just 4.5kg (10lbs) bare reel



YEAR 2 WARRANTY

Manual Caddy Style, Hose Reel Only

0122	-ID-	OD	L mtrs	PSI	£
CCWNR-1330	1/2"	7/8"	30	3000	266.85

- Heavy gauge, tubular all steel frame
- Highly visible yellow powder-coated finish
- 6" pneumatic tyres
- Full flow swivel assembly for maximum product delivery
- Stainless steel shaft, body in nickel-plated milled brass
- Fitted with Viton seals as standard, swivel has a twin O-ring design for extended trouble free service
- Swept riser assembly for easy hose installation
- Rolled and ribbed side discs for strength and rigidity
- Smooth and positive direct crank design
- Anti-slip rubber feet to prevent movement when extending hose
- Supplied as a bare reel, hose to suit application at extra cost



YEAR 2 WARRANTY

Hand Cranked, Wheeled, Hose Reel Only

0122	-ID-	OD	L mtrs	PSI	£
CCPOR-1345	1/2"	7/8"	45	700	499.40
CCPOR-1930	3/4"	1.1/8"	30	700	499.40

Stainless Steel Spring Rewind Reels

NB: hose not supplied.

Constructed in heavy gauge 304 stainless steel and other non-corroding materials, Redashe stainless steel hose reels are designed for use in harsh, corrosive environments or where hygiene is of primary importance.

They are ideally suited to wash down applications in food processing and chemical manufacturing and should also be specified for offshore and marine applications where salt spray rules out the use of standard steel models.

Features:

- Heavy duty 304 stainless steel construction
- Double supported solid 1" stainless steel axle
- Latching of hose at any length
- All working parts fully accessible for servicing
- Fully automatic hose rewind for neat and tidy storage
- Multi-position roller arm gives full range of mounting options
- Four direction non-sag roller guides reduce hose wear
- 1/4" stainless steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Externally mounted full flow swivel for maximum product delivery

See Hose Capacity Chart on Page 1434.

Maximum Working Pressure for Reel: 300 psi



Suitable for Air, Water, Steam, Food, Industry & Diesel, without Hose

0122	Inlet	£
SHL-N-450SS	1/2" BSP Female	1888.10

NB: hose not supplied.

Features:

- Non-corrosive stainless steel construction
- Four non-sag rollers reduce hose wear
- Ideal for food processing, wash down, chemical transfer and industrial solvent handling

See Hose Capacity Chart on Page 1434.

Maximum Working Pressure for Reel: 300 psi



E-Zy Reel Stainless Steel 808 Series Spring Rewind Hose Reel, without Hose

0122	Inlet	£
CSS808-450L	1/2" BSP Female	717.20

Features:

- Corrosion-resistant powder coating
- Guide arm adjustable handling up to nine positions
- Multi-position ratchet lock
- Spring fully enclosed and lubricated
- Wall, ceiling or floor mounted



808 Series Spring Rewind Hose Reels

0122	L mtrs	-ID-	OD	PSI	£
C808-350L	15	3/8"	3/8"	20	359.50
C808-450L	15	1/2"	1/2"	20	414.05
C808-350M	15	3/8"	3/8"	155	488.55
C808-450M	15	1/2"	1/2"	138	542.90

E-Zy Reel 208 Series Manual Rewind Hose Reels

- Excellent design, constructed from tubular and formed steel, which delivers superior strength and durability
- Corrosion resistant powder-coated finish, black as standard
- Full flow, brass swivel assembly, ensures maximum product delivery
- Suitable for wall, floor or workbench mounting, ideal for mobile vehicle applications and pressure washers
- Spring loaded locking pin prevents the hose from de-reeling
- Only 9.5kg (bare reel)

Maximum Working Pressure for Reel: 3,000 psi



Hose Reel Only

0122	To Suit	£
C208-3-100H	30m x 10mm	183.40
C208-4-65H	20m x 12.5mm	179.80

Hose Reel with Air & Water Hose

0122	L	£
C208-3-100H-AW	30m x 10mm	365.25
C208-4-65H-AW	20m x 12.5mm	303.60

Hose Reel with Diesel Hose

0122	L	£
C208-4-65H-D	20m x 12.5mm	326.25

12.3 Hose Reels

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep., Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE

HYDRAQUIP
HOSE & HYDRAULICS

www.hydraquip.co.uk