

# Cable Reels

**Nakoda**

## Polypropylene Series

- Constructed in tough UV-stabilised polypropylene
- Supplied with 6m fitted cable
- Latching of cable at any length
- Free run option available
- Low-effort rewind tension
- Pivoting wall bracket as standard
- Ideal for workshops and assembly lines
- Virtually maintenance free
- Supplied with UK standard plug and trailing socket
- 12 month manufacturer's warranty
- Amperage: 3 amp, cable in / 10 amp, cable out

Tech Sheet  
68097



### Minor Cable Reel, 240V

0520



L  
mtrs

£

HR-C-6-3C

240

6

142.35

- Constructed in tough UV-stabilised polypropylene
- Supplied with 10m fitted cable
- Latching of cable at any length
- Free run option available
- Low-effort rewind tension
- Pivoting wall bracket as standard
- Ideal for workshops and assembly lines
- Virtually maintenance free
- Supplied with UK standard plug and trailing socket
- 12 month manufacturer's warranty
- Amperage: 3 amp, cable in / 10 amp, cable out

Tech Sheet  
68098



### Master Plus Cable Reel, 240V

0520



L  
mtrs

£

HR-C-10-3C

240

10

186.10

- Constructed in tough UV-stabilised polypropylene
- Supplied with 18m fitted cable
- Latching of cable at any length
- Free run option available
- Low-effort rewind tension
- Pivoting wall bracket as standard
- Ideal for assembly lines and workshops
- Virtually maintenance free
- Supplied with UK standard plug and trailing socket
- 12 month manufacturer's warranty
- Amperage: 3 amp, cable in / 10 amp, cable out



Tech Sheet  
68099

### Special Cable Reel, 240V

0520



L  
mtrs

£

HR-C-18-3C

240

18

238.80

- Constructed in tough UV-stabilised polypropylene
- Supplied with 25m fitted cable
- Latching of cable at any length
- Free run option available
- Low-effort rewind tension
- Pivoting wall bracket as standard
- Ideal for workshops and assembly lines
- Virtually maintenance free
- Supplied with UK standard plug and trailing socket
- 12 month manufacturer's warranty
- Amperage: 3 amp, cable in / 10 amp, cable out



Tech Sheet  
68100

### Major Plus Cable Reel, 240V

0520



L  
mtrs

£

HR-C-25-3C

240

25

348.05

- Constructed in tough UV-stabilised polypropylene
- Supplied with 35m fitted cable
- Latching of cable at any length
- Free run option available
- Low-effort rewind tension
- Pivoting wall bracket as standard
- Ideal for workshops and assembly lines
- Virtually maintenance free
- Supplied with UK standard plug and trailing socket
- 12 month manufacturer's warranty
- Amperage: 3 amp, cable in / 10 amp, cable out



Tech Sheet  
68101

### Mega Cable Reel, 240V

0520



L  
mtrs

£

HR-C-35-3C

240

35

465.15

## ATEX Approved Grounding Reels

- Constructed in heavy-duty powder-coated mild steel
- Fully automatic spring rewind
- Wall, floor or ceiling mount options
- Full width roller guide as standard
- Single pedestal design
- ATEX II certified
- Latching of cable at various lengths
- Slotted mounting holes for easy installation
- Positive latching mechanism
- Adjustable cable stop
- Supplied with fitted cable
- 5 year manufacturer's warranty

Tech Sheet  
68103



### PUR-coated Copper Cable

0520

L  
mtrs

£

HR-535131-60152

15

677.70

HR-535131-60252

25

806.35

### PVC-coated Steel Cable

0520

L  
mtrs

£

HR-535141-60152

15

585.80

HR-535141-60252

25

718.60

## Tool Balancers

- DIN 15112, ISO EN 12100-1, CE, 2006/42/CE
- Die-cast aluminium case
- 2mm stainless steel support cable on HR-KTB-630, 631 and 632 units
- 2.5mm stainless steel support cable on HR-KTB-633, 634, 635, 636 and 637 units
- Continuous capacity adjustment from maximum value to minimum value
- Easily adjusted cable travel
- Four suspension points
- 12 months manufacturer's warranty



0520

kg

L  
mtrs

£

HR-KTB-630

0.4-1

1.6

81.05

HR-KTB-631

1-2

1.6

84.90

HR-KTB-632

2-3

1.6

89.15

HR-KTB-633

2-4

2.5

229.60

HR-KTB-634

4-6

2.5

235.35

HR-KTB-635

6-8

2.5

241.20

HR-KTB-636

8-10

2.5

246.95

HR-KTB-637

10-14

2.5

260.50

**HYDRAQUIP**  
HOSE & HYDRAULICS

www.hydraquip.co.uk