

Lever Lock Water Pump Couplings



JAYMAC
Industrial Hose & Accessories

Complete Connection Set



Maximum Working Pressure:
2" to 3.1/2" 20 bar
4" to 8" 12 bar

Galvanised with Standard Rubber Sealing Ring

0120	Coupling Size	To Suit Hose LD.	£
LLC2	50	2"	33.50
LLC33	76	3 Tail x 3"	51.35
LLC3312	89	3 Tail x 3.1/2"	62.70
LLC4	108	4"	85.45
LLC5	133	5"	166.95
LLC6	159	6"	156.75
LLC8	194	8"	399.60

Galvanised with Oil Resistant Rubber Sealing Ring

0120	Coupling Size	To Suit Hose LD.	£
LLC2OROR	50	2"	42.40
LLC33OROR	76	3 Tail x 3"	42.40
LLC4OROR	108	4"	73.95
LLC8OROR	194	8"	232.50



Jaymac Couplings provide a quick and easy way to join many lengths of hose together. They are commonly used for the pumping and transfer of water in the construction, road maintenance and general irrigation industries. They can also be used for loading and unloading road tankers.

Interchangeable with:
BAUER

Tech Sheet
20540



Maximum Working Temperature:
+80°C



Maximum Working Pressure:
2" to 3.1/2" 20 bar
4" to 8" 12 bar

Galvanised with Standard Rubber Sealing Ring

0372	Coupling Size	To Suit Hose LD.	£
LLZDUTY-LLC2	50	2"	30.80
LLZDUTY-LLC3	76	3"	55.80
LLZDUTY-LLC3312	89	3" Tail x 3.1/2"	61.70
LLZDUTY-LLC4	108	4"	80.55
LLZDUTY-LLC6	159	6"	153.65
LLZDUTY-LLC8	194	8"	231.70