

10 bar Water Suction Hose

Hose Assemblies & Hose

Hose assemblies are manufactured with black SBR tubes and ozone-resistant SBR covers.


The reinforcement is manufactured from high tensile textile cords embedded with steel helix wires for vacuum resistance.


All assemblies are fitted with male/female lever lock couplings.

Assemblies are available with any combination of fittings including flange, cam and groove.

Please contact our Business Development Team for a quote.

Material and test certification can be supplied.

 Working Temperature:
-30°C to +70°C

 Maximum Working Pressure:
150 psi



- Mechanical swage
- Decreases snagging
- Cleaner finish
- Added hose tail security
- No need for two indentations on the hose



Hose Assemblies (Ultra-lok Bands)

0180	Coupling Size	ID mm	OD mm	L mtrs	Assembly Max Working Pressure	£
WALLC2-3M	2"	51	62	3	10	117.35
WALLC2-6M	2"	51	62	6	10	163.65
WALLC3312-3M	3.1/2"	76	89	3	10	196.15
WALLC3312-6M	3.1/2"	76	89	6	10	273.05
WALLC4-3M	4"	102	115	3	10	234.75
WALLC4-6M	4"	102	115	6	10	392.35
WALLC6-3M	6"	152	168	3	7	434.20
WALLC6-6M	6"	152	168	6	7	804.75

Hose Only

0180	ID mm	OD mm	L mtrs	£
WA2-6M	51	62	6	125.55
WA3-6M	76	89	6	194.05
WA4-6M	102	115	6	246.70
WA6-3M	152	168	3	249.55
WA8-3M	203	222	3	406.70

Hose Assemblies (Swaged)

0372	Coupling Size	ID mm	OD mm	L mtrs	Assembly Max Working Pressure	£
WALLCSW2-3M	2"	51	62	3	10	112.55
WALLCSW2-6M	2"	51	62	6	10	172.70
WALLCSW3312-3M	3.1/2"	76	89	3	10	188.20
WALLCSW3312-6M	3.1/2"	76	89	6	10	279.10
WALLCSW4-3M	4"	102	115	3	10	247.40
WALLCSW4-6M	4"	102	115	6	10	371.75
WALLCSW6-3M	6"	152	168	3	7	522.10
WALLCSW6-6M	6"	152	168	6	7	771.90

Swage Rings



5555	To Suit Hose	£
SWAGE RING 2	2"	3.80
SWAGE RING 3	3"	4.35
SWAGE RING 4	4"	5.65
SWAGE RING 6	6"	8.10