

Shot Blast Couplings, Hose & Nozzle Holders

Shot Blast Couplings



Malleable Iron

0108	To Suit Hose O.D. mm	£
SHOT3101	39	19.25
SHOT3102	48	17.80
SHOT3103	56	25.65
SHOT3104	60	17.65

These couplings are designed for use on sandblast and cement placing hose.
Supplied with screws.

Maximum Working Pressure:
150 psi



Brass

6000	ID	OD mm	£
SBQ-34	3/4"	39	16.45



Nylon

0108	OD mm	£
SHOTCQP1	39	48.55
SHOTCQP2	48	44.95
SHOTCQP4	60	72.00

Threaded Couplings



Female Thread, Malleable Iron, BSPP

0108		£
SHOT3111	1.1/4"	21.70
SHOT3110	1.1/2"	15.00



Female Thread, Nylon, BSPP

0108		£
SHOTCFP	1.1/4"	55.80

Nozzle Holders



Alloy

0108		£
SD50-32A	48mm Coarse Thread	34.90
SD32-32A	48mm x 1.1/4" BSPP	22.75



Nylon

0108		£
NHP-34	33mm Coarse Thread	35.65
NHP-1	39mm Coarse Thread	63.95
HEP-1	39mm x 1.1/4" BSPP	32.60

Shot Blast Screws



0108	£
SHOTS	0.70

Safety Clips



0019		£
LUE-USC-1	3mm Wire Clip	1.20

Rubber Rings



0108	Size	£
SHOTRSDKD	SKD Standard Seals	1.20
SHOTRSDR2	SDR2 for CQP-1	6.85
SHOTRSDR3	SDR-3 for CQP-2/3/4, CFP/CFP-50	5.75

Spare Rubber Seal



Suits All Sizes	£
0019	
LUE-SKD-SEAL	3.35