

Pipe Clips & Fixing Systems



13. Clamps & Clips

Wall or Ceiling Mounted Pipe Clips

- Stainless steel universal clips for mounting stainless steel pipes to the wall or ceiling
- For use in situations where stainless steel mounting material is desired or required, such as food processing facilities, laboratories, the chemical industry, etc.

Advantages:

- Suitable for short-distance mounting

Tech Sheet
68176



BRS, Unlined, Stainless Steel

0713			£
38475	M8-M10	8-10	11.25
38476	M8-M10	12-14	11.70
38477	M8-M10	15-19	12.05
38478	M8-M10	20-25	12.45
38479	M8-M10	26-30	12.90
38480	M8-M10	32-36	13.50
38481	M8-M10	38-42	14.20
38482	M8-M10	44-49	14.25
38483	M8-M10	50-55	14.65
38484	M8-M10	56-61	15.10
38485	M8-M10	62-67	17.80
38486	M8-M10	68-73	18.40
38487	M8-M10	75-80	18.90
38488	M8-M10	82-86	19.50
38489	M8-M10	87-92	19.75
38490	M8-M10	95-102	23.60
38491	M8-M10	108-116	28.40
38492	M8-M10	121-127	29.95
38493	M8-M10	131-141	31.30
38494	M8-M10	159-163	34.10
38495	M8-M10	165-169	34.70
38496	M8-M10	192-202	46.70
38497	M8-M10	210-220	48.95

BSK-I clips are designed for plastic pipes with special TPE (thermoplastic elastomer) lining.

The BSK-I clip has easily removable plastic spacers between the two clip halves and can be transformed into a clenching clip without the need for tools.

Advantages:

- Special TPE lining with excellent low friction properties
- Transformable from sliding to clamping with easily removable spacer
- Fast assembly thanks to the patented click-spring locking system
- Noise reduction: 20 dB(A) with spacer, 18 dB(A) without spacer
- UV resistant
- Electronically zinc plated

BSK-I Clip Range

0713			£
37300	M8	16	7.65
37301	M8	20	8.15
37302	M8	25	8.80
37303	M8	32	9.75
37304	M8	40	10.85
37305	M8	50	12.15
37306	M8	56	14.00
37307	M8	63	16.05
37309	M8	75	16.60
37311	M8	90	18.75
37313	M8	110	23.45

- BSI-HDI clips are rubber lined, hot dip galvanized universal clips for mounting pipes to the wall or ceiling

Advantages:

- The clip has one or more strengthening ribs to achieve a strong working load
- Close fitting possible
- Noise suppression up to 17dB(A)

Working Temperature:
-40°C to +120°C



Tech Sheet
68174

BSI-HDI, Hot Dipped Galvanized

0713			£
38571	M8-M10	12-14	15.00
38572	M8-M10	15-19	15.40
38573	M8-M10	20-25	16.20
38574	M8-M10	26-30	17.05
38575	M8-M10	32-36	18.25
38576	M8-M10	38-43	19.45
38577	M8-M10	44-49	20.20
38578	M8-M10	50-55	21.55
38579	M8-M10	56-61	22.35
38580	M8-M10	62-67	26.50
38581	M8-M10	68-73	27.90
38582	M8-M10	75-80	29.15
38583	M8-M10	82-86	30.60
38584	M8-M10	87-92	31.50
38585	M8-M10	95-102	36.15
38586	M8-M10	108-116	38.90
38587	M8-M10	121-127	42.05
38588	M8-M10	131-141	44.90
38589	M8-M10	159-163	51.30
38590	M8-M10	165-168	52.35
38591	M8-M10	192-202	72.05
38592	M8-M10	210-220	77.95

Working Temperature:
-20°C to +100°C

Tech Sheet
68756



0713			£
37314	M8	125	25.85
37316	M8	160	31.50
37317	M8	200	40.45
37359	M10	75	15.75
37361	M10	90	18.70
37363	M10	110	23.45
37364	M10	125	27.75
37366	M10	160	35.45
37367	M10	200	48.20
37368	M10	250	57.80
37369	M10	315	73.70