Hydraulics

Hydraulic Quick Release

Couplings

Pneumatic

Quick Release Couplings

Air Prep., Media, Monito

& Test

KELM™

Pneumatics

Pneumatic

Lubrication



Dry Film Anti-stick

Use on guide rails on production lines to prevent jams; ideal for use as a non-tainting lubricant on packing and cardboard folding machines. Forms a dry non-staining film, exhibits excellent friction retardant properties.





Dry PTFE Lubricant







6140003500

23.30

Copper Anti-seize

Use on threaded fasteners to prevent seizing during prolonged maintenance intervals, in hostile/high humidity environments and areas subjected to high torque and/or temperatures.

Reduces friction and wear, good corrosion protection even in highly corrosive environments, Operational temperature range: -30°C to +1100°C.

- · 400ml are aerosols
- · 500gm are containers







High Temperature Anti-seize

0229		£
6190014010	400ml	12.65
6150001030	500g	17.70

Silicone Lubricant

Use for plastic-to-plastic lubrication, extra slip on chutes or slides, and on push fit pipes. Can also be used as a general mould release agent or as a cutting aid on paper/textile blades. Use on printing lines to reduce ink adhesion.















Ambergrease EXL

Use on critical and high load bearings and sliding surfaces. Suitable for use in applications where a longer service interval is required.

Exceptional load carrying capacity: 4-ball weld load >800Kg, Mean Hertz Load 125kg, Timken OK load: 25Kg, Highly visible red, NLGI type 2 grease, Lithium-Calcium Complex thickener.

Tech Sheet 20675

Extended Life, High Performance **Bearing Grease**





1

6150001010

Silicone Anti-stick

High concentration silicone lubricant for more demanding applications with higher loads or increased speeds e.g. robotic picking lines, conveyors, pallet guide rails and close tolerance fitting of large

Ideal for use where high standards of purity are essential, helps prevent line ams, inhibits adhesive build up on blades and sealers.

Tech Sheet 20676



Concentrated Silicone Lubricant







6140001500

400 21.15

Dry Moly

Use in higher load applications where PTFE lubricants would fail, but a dry film is still required. Use as a runningin treatment on rolling and sliding bearings.

Use as a lubricant for guides and joints; on wheel bearings on kiln carts; or lubrication of open gears

Operational temperature range: -150°C

Tech Sheet 20677

Molybdenum Disulphide Lubricant







6150002000 400

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for customer service department.

Multi-lube

Versatile lubricant for use in mechanical handling maintenance, cleans, lubricates and protects against corrosion.





Multi-purpose Lubricant







6170030020

White Spray Grease

Ideal for use on automotive door hinges. Use on runners, guide tracks, and other moving parts, NLGI grade 2 grease in an aerosol

20679



Multi-purpose White Grease

Tufcut is a range of specialist metal cutting

lubricants based on a mixture of lubricants, extreme pressure additives and anti-oxidants. The range

has been formulated to offer instant, ready-to-use

metal machining products that provide exceptional performance in demanding applications. All the

products are suitable for use on a wide range of

metals, including stainless and high carbon steels where "right first time" results are required.



6170030040

Tufcut

Tech Sheet

10365

FOOD

SAFE

0229

6150006000

6150005500

6150006500

6150006100

Metal Cutting Lubricant



350ml Liquid

400ml Spray

300ml Foam

500g Compound



10.30

Ring Main

Adaptors & Fittings

Stainless Steel Malleable

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compresso Equipment

£

22.00

20.05

21 90

17.35

Tools.

