

# Maintenance Paints



## Floor Coating

A ready to use solution for preparing your surface. Removes grease, oil & other contaminations.

Virtually odour free. Non-flammable. 6-8 m<sup>2</sup>/l coverage.

Tech Sheet  
60558



EpoxyShield<sup>®</sup> Cleaner/Degreaser, 5 Litre Tub

0209

£

RU-2901.5

73.10

Creates a surface profile that allows for maximum penetration & adhesion for the EpoxyShield<sup>®</sup> coatings.

Uses citric etch formula to avoid producing dangerous acids or fumes. Will not harm grass or plants.

Tech Sheet  
60557



EpoxyShield<sup>®</sup> Etching Solution, 5 Litre Tub

0209

£

RU-108.5

88.00

Multi-use epoxy resin repair mortar for concrete or stone. Unequalled hardness and epoxy bonding power. Epoxy Repair Mortar allows fast setting (3-6 hours), granite-hard permanent repairs to be made to badly cracked and worn concrete or stone floors. For use where conventional mortar or other fillers will loosen or fail. Anglo Epoxy Repair Mortar is virtually indestructible and ideal for repairs to factory floors, driveways, worn and broken steps, garage floors, sills, grouting in bolts and railings etc.

Tech Sheet  
60560



Epoxy Repair Mortar

0209

kg

£

RUS-5180.2.5	2.5	49.35
RUS-5180.5.0	5	92.25
RUS-5180.25	25	335.80

Speed patch gives a durable, fast setting repair to damaged floors, frost spalled, eroded and cracked concrete, steps, troughs, ramps covering etc.



Speed Patch

0209

kg

£

RUS-5150.1	10	77.95
RUS-5150.2	20	136.20

A quick easy way to fill holes in heavily used concrete floors inside and outside. No primer is required - just mix powder with water and pour into the hole. The rapid setting concrete repair bonds to damp or dry surfaces and can be applied at a thickness from surface edge to 100mm.

Tech Sheet  
60562



Speed Patch Pourable Grade 25kg

0209

£

RUS-AXPSP25	138.70
-------------	--------

Speed screed smooths uneven, damaged or worn concrete floors. A pour on durable re-surfacing material.

Suitable for interior or exterior use.

Tech Sheet  
60563



Speed Screed 25kg

0209

£

RUS-AXSS25	130.05
------------	--------

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.

Solvent-free Epoxy (2 part)  
For repairing fine cracks up to 3mm wide.

Dry in 3-4 hours.  
Coverage:  
25 linear metres (2mm wide, 5mm deep).

Tech Sheet  
60628



EpoxyShield<sup>®</sup> Fine Crack Repair Mortar, 500ml Tub

0209

£

RU-203010.05

47.00

Mineral-Acrylic.  
Easy to use - Add water, stir & ready.  
Traffic allowed after 24hrs.

10kg (1 part) 0.4m<sup>2</sup>.  
Recoat after 48 hrs.  
Note: to be recoated with 7100 Floor coating.

Tech Sheet  
60559



EpoxyShield<sup>®</sup> Concrete Repair Mortar, 10kg Tub

0209

£

RU-203012.10	101.85
--------------	--------

Rust-Oleum<sup>®</sup> Asphalt Repair is a durable bitumen-based patch repair product for use on exterior potholed asphalt and concrete. Ideal for potholes in roads, car parks, paths and other bituminous and concrete surfaces.

- Simple to use - no mixing required
- Repairs can be driven over immediately after application
- Ideal for repairs 10 mm - 70 mm
- Coverage approx. 0.5m<sup>2</sup> per 25kg at 24 mm thick
- Withstands heavy traffic

Tech Sheet  
60561



Asphalt Repair 25kg

0209

£

RUS-5410.25	95.75
-------------	-------

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep, Media, Monitor & Test

KELM<sup>™</sup> Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE