

Maintenance Paints



Hard Hat Maintenance Aerosols

- The quick anti-rust protector
- Ready to recoat after just 10 minutes, to handle after 30 minutes
- For new or slightly rusty surfaces
- Penetrates deeply into the surface and does not give rust a chance
- Lead and chromate free



Tech Sheet 60575

Anti-rust Primer, 500ml

0209		£
RUS-2169	Red	15.10
RUS-2182	Grey	15.10

Hard Hat Galvanizing Zincs

- Cathodic protection of bare and galvanized steel
- Resists 500 hours of salt spray testing (DIN 50021 SS)
- To recoat within one hour, brush version after 4 hours
- To recoat with Hard Hat metallic sprays



Tech Sheet 60572

Galva Zinc

0209			£
RUS-1085.1	1000	-	21.10
RUS-2185	-	500	18.20

- Zinc coating with sparkling aluminium particles
- The best compromise between a zinc spray and an aluminium spray
- Resists 340 hours of salt spray testing (DIN 50021 SS)



Tech Sheet 60571

Galva Zinc-aluminium

0209			£
RUS-1017.1	1000	-	22.50
RUS-2117	-	500	17.80

Hard Hat Maintenance Aerosols

- A durable adhesion on galvanized, stainless steel, aluminium, copper, hard PVC, glass and ceramics
- Ready to recoat after just 30 minutes
- Unique coverage: 5.5m² per aerosol
- To recoat with Hard Hat topcoats



Tech Sheet 60573

Sticker Adhesion, 500ml

0209	£
RUS-2102	14.00

- The super-fast zinc primer
- Tack free after just 5 minutes, to handle after 10 minutes
- Ideal for production and construction environments
- Resists 400 hours of salt spray testing (DIN 50021 SS)



Tech Sheet 60576

Galva Expresse, 500ml

0209	£
RUS-2180	15.45

- Appearance similar to new galvanized
- For touching up new galvanized
- Resists 310 hours of salt spray testing (DIN 50021 SS)
- Lower zinc contents, more aluminium



Tech Sheet 60574

Galva Plus, 500ml

0209		£
RUS-2120	Zinc Gloss	15.45

	2185 / 1085.1 GALVA ZINC	2180 GALVA EXPRESSE	2117 / 1017.1 GALVA ZINC-ALU	2120 GALVA PLUS
Appearance	Matt grey	Matt grey	Sparkling aluminium	Aluminium gloss
Zinc %	90%	68%	80%	54%
Aluminium %	0%	1%	10%	23%
Salt spray test	500 hrs.	400 hrs.	340 hrs.	310 hrs.
Tack free	10 min / 15 min	5 min	20 min / 30 min	15 min
To handle	30 min / 2 hrs.	10 min	60 min / 3 hrs.	60 min
Heat-resistant	450°C / 100°C	350°C	450°C / 100°C	150°C
Main advantage	Best protection	Quick drying	Good protection + finish	Finish like new galvanised

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.