

Hard Hat ® Topcoats

For use on engines, heat cannons, steam pipes, boilers, radiators, vents, barbecues and stoves.
750°C maximum temperature for short periods.



Tech Sheet
60579



Heat-resistant, 500ml

0209



£

RUS-7778	Black Satin Gloss	16.70
RUS-7715	Aluminium	17.30

Adheres to metal, wood, concrete, tile floors and parquet. Very quick drying (5 to 10 minutes).

For use on floors, steps, thresholds, etc.
Makes every surface non-skid in a second.



Anti-slip, 500ml

0209



£

RUS-2410	Transparent	21.60
RUS-2444	Safety Yellow	21.00
RUS-2479	Black	21.00

TIP: for maximum efficiency of fluorescent colours, spray over matt white and finish with Hard Hat ® clear coat.



Tech Sheet
60578



Fluorescent Top Coats, 500ml

0209



£

RUS-2233	Green	18.40
RUS-2222	Blue	18.40
RUS-2255	Orange	18.40
RUS-2264	Red	18.40
RUS-2242	Yellow	19.00

Hard Hat ® Metallics

Metallic sprays combine a bright metallic appearance with the durable protection of a standard topcoat.

- Gloss or sparkling metallic appearance
- To restore the metallic appearance
- For use on bare metal, galvanized, zinc primers or anti-rust primers



Tech Sheet
60577



Durable Protection, 500ml

0209



£

RUS-2111	Sparkling Aluminium	17.85
RUS-2115	Silver Aluminium	16.95

- Greater abrasion resistance
- Better anti-corrosion properties than other metallics
- Excellent UV resistance (does not discolour)
- Resists acids, chemicals and alkalis



Stainless Steel Coating, 500ml

0209

£

RUS-2116	18.00
----------	-------

Pipeline Identification Colours

Pipe Contents	RAL Code	CombiColor® Metal Protection	Hard Hat® Aerosols
Gas	RAL 1004	7349	2149
Fire Fighting	RAL 3000	7365	2165
Air	RAL 5012	7323	2123
Combustible Liquids	RAL 8001	7373	2173
Acids & Alkalis	RAL 4001	7363	2163
Water	RAL 6010	7334	2138
Other Liquids	RAL 9005	7379	2179
Steam	RAL 9006	7315	2114

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information please contact our customer service department.