

## Threadlockers

- A high strength, medium viscosity threadlocker and sealant. Ideally suited for use on tight fitting metal parts
- Oil tolerant
- Vibration resistant
- Lubricates threads for easier assembly
- Solvent free



Tech Sheet  
68166

### HM129, High Strength

0515



£

HM129

50

32.40

- Rapid curing adhesive designed to provide permanent locking and sealing of metal parts such as bearings, gears, pulleys and threaded components
- Toughened
- Rapid cure
- Ideal when bonding dissimilar materials
- Improved fatigue life



Tech Sheet  
68155

### A1046, Medium Strength

0515



£

A1046

50

32.40

- Designed for the locking and sealing of metal parts, and ideally suited for use on components that need to be dismantled for maintenance
- Excellent chemical resistance
- Vibration resistant
- Lubricates threads for easier assembly
- Provides corrosion protection
- WRAS listed for contact with potable water



Tech Sheet  
68149

### A130, Low Strength

0515



£

A130

50

32.40

A130-10

10

6.80

- A rapid curing adhesive designed to lock and seal metal parts that subsequently may need to be dismantled for maintenance
- Suitable for small hydraulic and pneumatic fittings
- Rapid cure
- Vibration resistant
- Lubricates threads for easier assembly
- Provides corrosion protection
- WRAS listed for contact with potable water



Tech Sheet  
68153

### A1042, Rapid Cure

0515



£

A1042

50

32.40

- A rapid curing sealant designed to lock and seal metal pipe connections
- Instant low pressure seal
- Does not shred or dry out
- Excellent chemical resistance
- Seals against most gasses and liquids
- WRAS listed for contact with potable water



Tech Sheet  
68154

### A1044, High Strength

0515



£

A1044

50

32.40

- Primarily designed for use on metal surfaces
- Has excellent resistance to peel and impact forces, as well as being capable of resisting the thermal stresses that may be generated when bonding dissimilar surfaces
- Toughened
- Thixotropic
- Good adhesion to copper and aluminium
- Improved fatigue life
- WRAS listed for contact with potable water



Tech Sheet  
68164

### F202, High Strength

0515



£

F202

50

32.40

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information, please contact our customer service department.