

Thread Sticks

LOCTITE®

Threadlocker Sticks

- Effective on all types of metal threaded fasteners. Recommended where disassembly is required. Machine tools and presses, pumps and compressors, mounting bolts and gear boxes
- For use on threads up to M50
- Functional strength 6 hours
- Long term temperature resistance +150°C

**Tech Sheet
67925**


248, Medium Strength

0753		£
LOC-248	19	20.95

- Effective on all types of metal threaded fasteners. Recommended for use where regular removal for maintenance is not required. Suspension bolts, motor transmission and pump mounts, bearing cap bolts and studs
- For use on threads up to M50
- Functional strength 24 hours
- Long term temperature resistance +150°C

**Tech Sheet
67926**


268, High Strength

0753		£
LOC-268	19	20.95

Thread Sealant Stick

- Recommended for all coarse metal pipe threads where disassembly is required. Ideal for use in a broad range of industries including chemical, processing, waste water treatment and automotive.
- For use on threads up to 3"
- Substrate to be sealed: Metal
- Instant low pressure seal
- Low disassembly strength
- Long term temperature resistance +150°C

**Tech Sheet
67927**


561, Instant Bonding

0753		£
LOC-561	19	13.50

Anti-Seize Sticks

- Copper based anti-seize for screws, nuts, pipes, heat exchangers etc.
- Sold lubricating agent containing copper and graphite
- N.L.G.I. Class 1

 Working Temperature:
-30°C to +930°C

**Tech Sheet
67928**

8065, C5-A Copper, High Temperature

0753		£
LOC-8065	20	11.25

243 Threadlocker

Particularly suitable on all metal threaded fasteners. Prevents loosening on vibrating parts such as pumps, motor mounting bolts, gear boxes or presses. Recommended for use where disassembly with hand tools is required for servicing and where parts are contaminated with oil.

- Resists vibration
- Single part – clean and easy to apply
- Can be used on all sizes of fasteners – reduces inventory costs
- Seals threads allows through-hole tapping

**Tech Sheet
67929**


Medium Strength

0753		£
LOC-135279	10	11.50
LOC-135278	50	51.50

270 Threadlocker

Particularly suitable for use on all metal fasteners (including stainless steels and those with protective coatings such as Zinc) where regular removal for maintenance is not required. Recommended for permanently locking studs on engine blocks and pump housings.

- Resists vibration
- Single part – clean and easy to apply
- Can be used on all sizes of fasteners – reduces inventory costs
- Seals threads allows through-hole tapping

**Tech Sheet
67930**


High Strength

0753		£
LOC-267380	10	11.35
LOC-232515	50	50.40

Due to restrictions imposed by the Transport of Dangerous Goods Act, these products are available for delivery to MAINLAND UK ONLY. For further information, please contact our customer service department.