

Wash Down Equipment



Twin Pressure Washer Lances



Maximum Working Temperature: +60°C



Maximum Working Pressure: 250 bar

Flow: 35 lpm



Stainless Steel Twin Lance with Top Control, BSPP

1369



£

SSTLTC

1/4"

121.15

Flow: 45 lpm



Stainless Steel Twin Lance with Handle, BSPP

1369



£

SSTLH

1/4"

128.70

Flow: 45 lpm



Zinc Plated Twin Lance with Handle, BSPP

1369



£

ZPTLH

1/4"

75.75

Flow: 45 lpm



Zinc Plated Twin Lance with Top Control, BSPP

1369



£

ZPTLTC

1/4"

75.75

Pressure Washer Lances

All supplied with 1/4" female thread nozzle holder and protector.
1/4" Male thread inlet.



Maximum Working Temperature: +150°C



Maximum Working Pressure: 250 bar

Maximum Flow: 40 lpm



Straight with Moulded Grip Zinc Plated

1369



900

No. of Grips

1

£

SL-2

29.85



Bent End with Vented Grip Zinc Plated

1369



900

No. of Grips

1

£

SL-7

40.85

SL-8

96.65



Bent End with Moulded Grip Zinc Plated

1369



900

No. of Grips

1

£

SL-3

32.85

SL-4

46.80



Bent End with Moulded Grip Stainless Steel

1369



900

No. of Grips

1

£

SL-10

54.60

SL-11

68.40



Bent End with Hollow Grip Zinc Plated

1369



700

No. of Grips

1

£

SL-5

39.35



Straight with Moulded Grip Stainless Steel

1369



900

No. of Grips

1

£

SL-12

Screw Guard 57.55

SL-13

Slide on Guard 59.25

Heavy Duty Foam Injection Bottle

- Heavy duty foam injection bottle connects easily to your existing pressure washer lance or gun.
- Variable angle spray pattern nozzle.
- Adjustable detergent displacement.
- Foam bottle sprays foam all over the vehicle creating the "snow bath effect".
- 1/4" BSPP male inlet connection.
- 1 litre bottle.
- 1/4" x 1/4" adaptor removable for ease. Other adaptors can be fitted.



Maximum Working Temperature: +60°C



Maximum Working Pressure: 275 bar



Male, BSPP

1369



1/4"

£

FGB-1

71.55