

Wash Down Equipment



High Pressure Spray Nozzles

Stainless steel, 1/4" male thread with a hardened steel insert for longer life and better accuracy, suitable for single and double lances.



Stainless Steel, 1/4" BSPT Male

1369		@50bar LPM	@100bar LPM	@150bar LPM	£
2020-2982	0°	8	11.3	13.8	14.40
2020-2990	0°	8.7	12.4	15.2	14.40
2020-3014	0°	9.6	13.6	16.7	14.40
2020-3089	15°	8	11.3	13.8	14.40
2020-3105	15°	8.7	12.4	15.2	14.40
2020-3113	15°	9.6	13.6	16.7	14.40
2020-3139	25°	8	11.3	13.8	14.40
2020-3147	25°	8.7	12.4	15.2	14.40
2020-3154	25°	9.6	13.6	16.7	14.40
2020-3162	40°	8	11.3	13.8	14.40
2020-3188	40°	8.7	12.4	15.2	14.40
2020-3204	40°	9.6	13.6	16.7	14.40

Brass, 1/4" BSPT Male



1369	£
2021-8061	12.25

Rotating Head Nozzle

Maximum Working Temperature: +90°C
Flow: 45 lpm



Maximum Working Pressure: 345 bar

1/4" Female, BSPP

1369	£
9202L	284.45

Fixed Head Nozzle

Maximum Working Temperature: +90°C
Flow: 45 lpm



Maximum Working Pressure: 280 bar

1/4" Female, BSPP

1369	£
9203L	128.95

1/4" High Pressure Quick Release Nozzles



A Series Nozzles

1369		@50bar LPM	@100bar LPM	@150bar LPM		£
A00050	0°	8	11.3	13.8	Red	7.20
A00055	0°	8.7	12.4	15.2	Red	7.20
A00060	0°	9.6	13.6	16.7	Red	7.20
A15050	15°	8	11.3	13.8	Yellow	7.20
A15055	15°	8.7	12.4	15.2	Yellow	7.20
A15060	15°	9.6	13.6	16.7	Yellow	7.20
A25050	25°	8	11.3	13.8	Green	7.20
A25055	25°	8.7	12.4	15.2	Green	7.20
A25060	25°	9.6	13.6	16.7	Green	7.20
A40050	40°	8	11.3	13.8	White	7.20
A40055	40°	8.7	12.4	15.2	White	7.20
A40060	40°	9.6	13.6	16.7	White	7.20

Adjustable Pressure Nozzle

Flow: 25 lpm

Maximum Working Temperature: +60°C



Maximum Working Pressure: 200 bar

1/4" Female, BSPP

1369	£
CDQC-14	28.35

Fixed Jet Pressure Nozzle

Flow: 35 lpm

Maximum Working Temperature: +90°C



Maximum Working Pressure: 380 bar

Drain Cleaning Head, 1 Forward 3 Rear, 1/4" Female

1369	£
CDQP001-14	15.05

Drain Nozzles

Maximum Working Temperature: +95°C

Maximum Working Pressure: 385 bar




Fixed, BSPP

1369		Nozzle Diameter mm	£
SJN-2-045	1/8"	0.7	14.90
SJN-2-050	1/8"	0.75	14.90
SJN-2-055	1/8"	0.8	14.90
SJN-4-045	1/4"	0.7	17.70
SJN-4-050	1/4"	0.75	17.70
SJN-4-055	1/4"	0.8	17.70
SJN-6-045	3/8"	0.7	25.20
SJN-6-050	3/8"	0.75	25.20
SJN-6-055	3/8"	0.8	25.20

Maximum Working Temperature: +95°C

Maximum Working Pressure: 280 bar



Rotating, BSPP

1369		Nozzle Diameter mm	£
RSJN-2-045	1/8"	0.7	23.25
RSJN-2-050	1/8"	0.75	23.25
RSJN-2-055	1/8"	0.8	23.25
RSJN-4-045	1/4"	0.7	28.00
RSJN-4-050	1/4"	0.75	28.00
RSJN-4-055	1/4"	0.8	28.00
RSJN-6-045	3/8"	0.7	34.55
RSJN-6-050	3/8"	0.75	34.55