
Fuel Dispensing Hose & Gravity Hose Kits



Oil resistant rubber alloy, suitable for use with diesel, air and water delivery. Cover: black, weather and ozone resistant with purple strip. Safety Factor: 3-1.





3/4" BSPP Male/Male x 3/4" ID Replacement Hose

0225	L mtrs	\mathfrak{L}
RTDH-34-3	3	17.65
RTDH-34-4	4	20.65
RTDH-34-5	5	23.85
RTDH-34-6	6	27.00

1" BSPP Male/Male x 1" ID Replacement Hose

0225	L	\mathfrak{L}
RTDH-1-3	3	26.60
RTDH-1-4	4	31.00
RTDH-1-5	5	35.40
RTDH-1-6	6	39.80
RTDH-1-8	8	48.65
RTDH-1-10	10	57.55
RTDH-1-12	12	66.35

1" BSPP Male/Male x 1" ID Super Flexible Deluxe Replacement Hose

0225	L	£
DRTDH-1-3	3	42.10
DRTDH-1-4	4	51.65
DRTDH-1-5	5	61.30
DRTDH-1-6	6	70.85
DRTDH-1-8	8	90.00
DRTDH-1-10	10	109.15
DRTDH-1-12	12	128.40

Gravity Hose Kits





HOSE INFO. Maximum Working Pressure: 20 bar

Oil resistant rubber alloy, suitable for use with diesel, air and water delivery. Cover: black, weather and ozone resistant with purple strip. Safety Factor: 3-1

NOZZLE INFO. Maximum Working Pressure: 142 psi (10 bar)

> Maximum Flow: 150 L/min

Manual trigger, suitable for use with diesel, biodiesel up to B100 and oils to SAE 90.

1" BSPP Male/Male x 1" ID Deluxe **Gravity Hose Kits**

0225	L	3
DASS-RTDH-1-3	3	116.25
DASS-RTDH-1-4	4	125.95
DASS-RTDH-1-5	5	135.40
DASS-RTDH-1-6	6	145.00
DASS-RTDH-1-8	8	164.20
DASS-RTDH-1-10	10	183.40
DASS-RTDH-1-12	12	202.60
DASS-RTDF' 1 17	4-	244.45

Working

HOSE INFO. Temperature: -20°C to +60°C



NOZZLE INFO. Maximum Working Pressure: 58 psi (4 bar)

Maximum Flow: 80 L/min Manual trigger, suitable for use with diesel.

1" BSPP Male/Male x 1" ID **Gravity Hose Kits**

0225	L mtrs	\mathfrak{Z}
ASS-RTDH-1-3	3	64.05
ASS-RTDH-1-4	4	68.45
ASS-RTDH-1-5	5	72.90
ASS-RTDH-1-6	6	77.20
ASS-RTDH-1-8	8	86.15
ASS-RTDH-1-10	10	95.15
ASS-RTDH-1-12	12	103.85
ASS-RTDH-1-15	15	117.00

www.hydraquip.co.uk