

# Fuelling Equipment & Accessories

## Swivel Hose Fittings

Greatly eases handling and reduces hose wear and kinking.  
All have parallel threads except (SWIV.15A) which has a taper male and parallel Female.



Maximum Working Pressure:  
87 psi (6 bar)



0225	Female	Male	£
SWIV.3A	3/4"	3/4"	18.20
SWIV.13A	1"	3/4"	18.20
SWIV.31A	3/4"	1"	18.20
SWIV.1A	1"	1"	18.20
SWIV.15A	1.1/2"	1.1/2"	60.95

## Jointing Compound

General purpose jointing & thread sealing compound.  
Recommended for diesel, oil, water & steam.  
NOT suitable with ethanol.

Fully waterproof & MOD approved.  
250ml screw top tins with brush applicator.  
500ml tins without brush applicator.



0225	ml	£
HELD	250	28.20
HELD.500	500	42.35

## Fuel Lockout Valve



BSPP

0225	£
FLV-1	23.15

## Goodyear Softwall Diesel Hoses

Only suitable with diesel or biodiesel up to B30.  
Ideal for use on economy fuel dispensers.  
Machine swaged ends for long life.  
Electrically bonded.  
3/4" or 1" BSPT male ends.  
Not steel braided.  
Not suitable for use with petrol.



Maximum Working Pressure:  
50 psi (3.5 bar)



BSPT

0225	L mtrs	£
CH4.19	4	79.95
CH6.19	6	118.75
CH4.25	4	100.25
CH6.25	6	164.35

## Goodyear Steel Braided Hoses

Suitable with petrol, diesel, biodiesel up to B100 & ethanol.

Tested & approved to EN1360 (Supersedes BS3395)  
BSP parallel zinc plated "swaged for life" end fittings.

Smooth wipe clean covering.

Excellent fuel & weather resistance.

Steel braiding provides excellent protection against vandalism & the theft of nozzles by cutting through the hoses.

Can be used with ethanol blended fuels.



Maximum Working Pressure:  
230 psi (15.8 bar)



BSPP

0225	L mtrs	£
PH12.3/4	3.66	161.15
PH20.3/4	6.1	246.75
PH12.1	3.66	210.40
PH20.1	6.1	333.90

## Gravity Dispensing Hose

Gravity dispensing hoses 25mm (1") bore, excellent flexibility to ease handling and strong enough to resist kinking. Supplied with 1" BSPT male end fittings are machine banded on to the hose.



Maximum Temperature:  
-15°C to +60°C



Maximum Working Pressure:  
43.5 psi

Tech Sheet  
1173



1" BSPT

0225	L mtrs	£
GDH-4	4	52.10
GDH-5	5	63.35
GDH-6	6	75.00

## Gravity Fuel Kits

Only suitable with diesel or biodiesel up to B30.  
Provides simple & quick diesel dispensing from gravity tanks.

Kit includes: hose, valve, nozzle & PTFE tape.  
25mm bore delivery hose.



Working Temperature:  
-25°C to +45°C



Maximum Working Pressure:  
50 psi (3.5 bar)

Tech Sheet  
1170



For use with Diesel/Gasoil

0225	L mtrs	£
2019-9337	3	80.60
2019-9360	5	93.20