

Manual Transfer Pumps

Gear Oil Pump

Suitable with high viscosity oils, ideal for filling gear boxes.
 Polypropylene pump, mild steel piston & nitrile seals.
 Dispenses approximately 100ml per stroke.
 Has a 1.5m outlet hose with spout.
 Spout can be drained by locating back into pump body.
 Supplied with two adaptors as standard: One fits most 25L external Plysu threads (60mm dia). The other fits most 25L Trisure/Valorex thread (56mm dia).
 Option: universal adaptor, locks onto any external thread that is less than 61mm dia.



0225		£
HPGO	Pump	109.30
ADAPT.UNIL	Adaptor	22.40

Oil Suction Gun

For getting oil in/out of gearboxes, transfer cases & differentials.
 • Suitable for use with non corrosive liquids.
 • Capacity 500cc with 300mm PVC hose.
 • Deluxe lip seal provides maximum suction.
 • Steel barrel in premium powder coated finish.
 • Fully serviceable.
 • No priming required.



0225	£
OSG	14.70

Liquid Suction/Extraction Units

Novel device that both sucks & stores extracted liquids.
 Suitable for fuels, water, oils and many other liquids.
 Removes: Oil from vehicles, lawn mowers, motorbikes, hydraulic reservoirs without draining, simply insert the suction pipes in the dipstick hole.
 Water from bundled fuel tanks/cabinets, fish tanks, bilges & otherwise inaccessible areas. Fuel spillages from bundled tanks/fill point cabinets.
 Can even suck up surface puddles.
 Prime the handle & watch it work.
 Supplied with suction probes to fit most applications.
 Lightweight & portable. 17 litre version has castors.
 When full, remove top plug to pour out the contents.



Suction/Extraction Units

0225	Capacity	£
HP.SUC2	2.7 Litre	67.35
HP.SUC6	6 Litre	133.65
HP.SUC17	17 Litre	213.90

Same as 6 litre capacity version (HP.SUC6) but can also empty it's own tank as is bi-directional. Automatically fills (sucks) & empties (discharge).
 Prime the handle & watch it work. (May need to prime handle again when discharging).
 Sucks up 6 litres of water in 2.1/2 mins & empties in the same time.



Suction/Extraction/Discharge Unit

0225	Capacity	£
HP.SUC6B	6 Litre	212.75



Redashe

Features:
 Pumps diesel, petrol, kerosene and lubricating oils up to SAE 30.
 Designed to fit 205 litre (55 US gal) or 60 litre (16 US gal) drums.
 Ideal for high volume aviation transfer fuel.
 Pumps easily in both directions.
 Supplied with a 2.4m (8ft) antistatic rubber delivery hose and nozzle and 1050mm (3.5ft) two piece threaded suction tube.
 Lockable handle and built in nozzle holder.
 In-built strainer.
 50mm (2") adjustable bung adaptor.
 Output: up to 100 litres (26 US gal) per minute or 1 litre (1 quart) per rotation.
 Outlet port: 25mm (1").

GP Rapid-Flo

0122	£
GP-RAPIDFLO	733.25

Hydraulics
Hydraulic Quick Release Couplings
Pneumatic Quick Release Couplings
Air Prep, Media, Monitor & Test
KELM™ Pneumatics
Pneumatic & Vacuum Equipment
Valves
Ring Main Systems
Adaptors & Fittings
Stainless Steel
Malleable Iron
Hose, Tubing & Couplings
Clamps & Clips
Sprays & Adhesives
Blow Guns, Vacuum & Nozzles
Pressure Wash, Fuelling & Lubrication
Air Tools & Compressor Equipment
Tools, Hardware & PPE