

Electrical Transfer Pumps

12V Submersible Transfer Pump

Only suitable with diesel, biodiesel B30 & water to 80°C.
Maximum Flow: 18 L/min. Length 145mm, diameter 47.5mm.

12V centrifugal submersible pump.
3m outlet hose (1/2"). (500 hour life expectancy).
4m long battery cable & clips. Weight 0.6kgs.
Continuously rated for periods up to 1 hour.

NOTE:
DO NOT RUN DRY



Maximum Working Pressure:
15 psi (1 bar)



0225			£
12SP18	12V	18	130.45

Electric Oil Transfer Pump

Designed for pumping and transferring all grades of oils up to SAE 90. Suitable for lubricating oils, hydraulic oils, gear oils etc. Complete with on/off switch and internal bypass, it has 3/4" BSPP threaded ports and is also supplied with a pair of 1" hose tails. Pumping rate depends on grade of oil & temperature.

• IP55 Rated

Tech Sheet
1174

2033-5279



VISCO.110

0225		£
2033-5279	230V	701.00
VISCO.110	110V	997.10

Portable Pump Kits

Only suitable with diesel or biodiesel up to B30.
Choice of 12V or 24V.

40 L/min pumping speed.
Sturdy steel case complete with carry handle
On/off switch & bypass valve.
2 metre long battery lead & crocodile clips.
6 metre of suction/delivery hose.
Suction foot valve & strainer must be fitted or warranty is void.
Maximum Run Time: 30 mins.



Manual, BSPP

0225			£
12PA.KIT1C	1"	12V	363.25
24PA.KIT1C	1"	24V	291.40

Professional Battery Diesel Pump Kits

For use with diesel, empties a 205L drum in 5 mins.
40 L/min. 4m battery lead with crocodile clips.
Carry handle, on/off switch, bypass valve.
Suction/delivery hose 6 metre in total.
Aluminium nozzle with hose swivel.
Complete kit for barrel/portable transfer.
Maximum run time: 30 mins.



0225			£
12PA.KIT1B	12V	40	291.40
24PA.KIT1B	24V	40	291.40

High Speed Battery Diesel Pump Kits

Only suitable with diesel or biodiesel up to B30.
Maximum Flow: 70 L/min. 12V.
1" BSPF inlet & outlet flanges.
Direct drive vane pumping unit with bypass valve.
Switch, 4m long battery cable & crocodile clips.
Weatherproof for outdoor use.
Maximum run time: 30 mins.
Kit includes 7m suction/delivery hose, foot valve & strainer.
Choose manual or automatic nozzle kit.



0225	Nozzle	£
12BIKIT	Manual	666.75
12BIKIT2	Automatic	1292.40

Battery Transfer Pumps

Only suitable with diesel or biodiesel up to B30.
Ideal for mounting into plant equipment, excavators etc.
Maximum Flow: 40 L/min.
3/4" BSPF ports.
Choose 12V or 24V.
Direct drive vane pumping unit with bypass valve.
Foot mounting plate.
Weatherproof to IP54 for outdoor use.
Complete with switch, carry handle.
4m long battery cable & crocodile clips.
Maximum run time: 30 mins.



0225		£
12PA.BARE	12V	194.70
24PA.BARE	24V	194.70