

Greasing & Lubrication Equipment

High Pressure Hose & Accessories



None Filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382			
LU-1710	4	8.75	121.70
LU-1730	6.3	11.3	151.60

Grease Filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382			
LU-1720	4	8.75	173.30

Straight Inserts, Steel Zinc Plated



0382			
LU-1740	4	8.75	5.25
LU-1750	6	8.75	5.70



Straight Inserts, Stainless Steel

0382			
LU-1760SS	6	8.75	22.35



90° Inserts, Steel Zinc Plated

0382			
LU-1780	6	8.75	12.60
LU-1790	8	11.3	21.10



Ferrule, Zinc Plated

0382		
LU-1800	8.75	6.15
LU-1810	11.3	14.10



Ferrule, Stainless Steel

0382		
LU-1820SS	8.75	22.35
LU-1830SS	11.3	45.80

Lubrication & Pumping Equipment

Three Inch Air Motor, provides more power to create better flow.

NXT Air Valve, designed to reduce icing in continuous use applications and uses less air than competitive pumps for better efficiency. Easy to repair or replace without tearing down internal pump components for less downtime.

Modular Air Valve, air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle free installations.

Built-In Thermal Relief and Inlet Strainer, built-in thermal relief protects your equipment from thermal expansion without the need to buy and install an additional kit.

Inlet strainer (oil only) is built-in to protect pump from contaminants that can damage your pump.

Connections:

Air Line 1/4" BSP
Fluid Outlet 1/2" BSP
Inlet 1" BSP

900mm plastic down tube (can be cut down as required).



LD Range Oil Pumps

0382			
24G581	3:1	9.8	765.75
24G593	5:1	7.6	807.10



Wall Mount Bracket

0382		
24F910	24G5 Series Pumps	213.85

Remote Grease Systems

Contents:

- 1 x 1/8" BSP 2 way block
- 2 x 1/8" BSP straight grease nipples
- 4 x 1/8" BSP x 6mm straights
- 2 x M8 x 1 straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube.



2 Point

0382	
BAT03	157.35

Contents:

- 1 x 1/8" BSP 6 way block.
- 6 x 1/8" BSP straight grease nipples.
- 6 x M6 x 1 x 6mm straight compression fittings.
- 6 x 1/8" BSP x 6mm straight compression fittings.
- 30 metre of 6 x 3mm semi rigid black nylon tube.



6 Point

0382	
BAT06	189.00

Manual Grease System

Contents:

- 1 x 1 litre manual pump.
- 1 x 4 way grease block.
- 1 x 81-5261-1/4 x 6mm straight.
- 8 x 1/8" BSP x 6mm fitting.
- 30 metre coils of 6 x 3 semi rigid black nylon tube.
- 6 x 1 way pipe clips.

Suitable for soft grease NLGI NO 000,00,0
For use on small machinery, direct feed on to bearings.
1.00cc delivery per stroke.
Max discharge pressure 150 bar.



4 Point

0382	
PROG12	751.60