Hydraulics

Hydraulic Quick Release

Quick Release Couplings

Air Prep., Media, Monitor

& Test

KELM™ Pneumatics Pneumatio & Vacuum Equipment

Systems

Malleable

Hose, Tubing & Couplings

Sprays & Adhesives Blow Guns Nozzles

Air Tools & Compressor Equipment

Couplings Pneumatic

Automatic Lubricant Dispensers



MD 2000 ULTIMATE MODEL 125

Page Tech Sheet 60409

Series Multi-point Ultimate Luber

The Ultimate Luber is a powerful, motor-driven automatic lubricator which is refillable using a standard grease gun. motor delivers grease to a fixed displacement pump which produces pressures up to 100 bar. This power allows th feed lines and to cycle progressive distributors to feed several bearings consecutively. When a dispensing cycle is selected, programmed intervals. During each cycle, it dispenses approximately 1.25cc of grease. Neither temperature nor all Its microprocessor controlled, energy-efficient power allows the Ultimate Luber to drive lubricant through long the Ultimate Luber will activate at nor altitude will affect the lubricant output. **Features**

MD-2000 ULTIMATE

MODEL 500

MD-2000 ULTIMATE

- · Powerful, motor-driven lubricator
- · Fully self-contained lubricator with replaceable battery pack
- Refillable using a standard grease gun (no tools needed)
- Available in three sizes: 125cc, 250cc or 500cc
- Multiple settings to empty from 15 days to 2 years
- LEDs indicate correct operation, low battery and low temperature
- Single or multi-point configuration
- Capable of servicing single-point applications up to 30ft (9m) away and multi-point applications up to 20ft (6m) away
- Optional remote power/remote control versions available
- · Suitable for indoor and outdoor use

Advantages

- Powerful automatic lubricator at 100 bar
- Refillable on site with a grease gun
- Feed up to 12 points from single unit
- · Incredibly durable; lasts many refills
- · Fill with any brand of grease
- No direct competition in pressure and refillability available

Working Temperature: -40°C to +55°C



Maximum Working Pressure: 100 bar

Motor-driven Lubricant Dispenser, Empty, Refillable

0483		Capacity	Operation	\mathfrak{L}
US-125	1/4"	125cc	15 Days to 24 Months	319.60
US-250	1/4"	250cc	15 Days to 24 Months	472.60
US-500	1/4"	500cc	15 Days to 24 Months	515.50



	0483	\{ \}	Capacity	Operation	£
	US-125	1/4"	125cc	15 Days to 24 Months	319.60
	US-250	1/4"	250cc	15 Days to 24 Months	472.60
Ī	US-500	1/4"	500cc	15 Days to 24 Months	515.50









