

# Fag Filters

## Diesel Oil Filters - Series 20100-20150



Maximum Working Pressure: 2 bar



Aluminium, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20103/AL-100UM	1/4"	100	48	13.85
20101/AL-100UM	3/8"	100	48	13.85
20103AL4-44UM	1/4"	44	48	15.95
20101AL4-44UM	3/8"	44	48	15.95
20103CAL-15UM	1/4"	15	228	18.30
20101CAL-15UM	3/8"	15	228	15.25
20153/AL-100UM	1/4"	100	24	15.05
20151/AL-100UM	3/8"	100	24	12.80



Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20103/PL-100UM	1/4"	100	48	12.70
20101/PL-100UM	3/8"	100	48	12.70
20103PL4-44UM	1/4"	44	48	15.05
20101PL4-44UM	3/8"	44	48	15.05
20103CPL-15UM	1/4"	15	228	14.15
20101CPL-15UM	3/8"	15	228	14.15
20153/PL-100UM	1/4"	100	24	14.40
20151/PL-100UM	3/8"	100	24	14.40



Maximum Working Pressure: 1 bar



Plastic Superior Metocene Bowl, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20103/PE-100UM	1/4"	100	48	10.20
20101/PE-100UM	3/8"	100	48	15.80
20103CPE-15UM	1/4"	15	228	11.25
20101CPE-15UM	3/8"	15	228	11.25
20153/PE-100UM	1/4"	100	24	11.10
20151/PE-100UM	3/8"	100	24	9.35

## Diesel Oil Filters - Series 20200



Maximum Working Pressure: 2 bar



Aluminium, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20201/AL-100UM	3/8"	100	105	25.05
20202/AL-100UM	1/2"	100	105	25.75
20201AL4-44UM	3/8"	44	105	28.90
20202AL4-44UM	1/2"	44	105	28.90
20201CAL-15UM	3/8"	15	235	29.50
20202CAL-15UM	1/2"	15	235	29.50



Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20201/PL-100UM	3/8"	100	105	24.50
20202/PL-100UM	1/2"	100	105	24.50
20201PL4-44UM	3/8"	44	105	27.90
20202PL4-44UM	1/2"	44	105	19.85
20201CPL-15UM	3/8"	15	235	27.20
20202CPL-15UM	1/2"	15	235	27.20

## Diesel Oil Filters - Series 20210



Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl with Water Drain Valve, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20211/PL-100UM	3/8"	100	105	29.75
20212/PL-100UM	1/2"	100	105	29.75
20211PL4-44UM	3/8"	44	105	39.50
20212PL4-44UM	1/2"	44	105	33.00
20211CPL-15UM	3/8"	15	235	32.50
20212CPL-15UM	1/2"	15	235	32.50

## Diesel Oil Filters with Cock & Check Valve - Series 20250



Maximum Working Pressure: 2 bar



Aluminium, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20250/AL-100UM	3/8"	100	105	40.95
20250ALAL4-44UM	3/8"	44	105	53.95
20250CAL-15UM	3/8"	15	235	53.15



Maximum Working Pressure: 1 bar



Plastic Standard Tenite Bowl, BSPP

0270



µm

Filter Surface Area cm<sup>2</sup>

£

20250/PL-100UM	3/8"	100	105	49.25
20250PL4-44UM	3/8"	44	105	52.65
20250CPL-15UM	3/8"	15	235	43.40

N.B. Oil viton seal filters are available upon request.