

# Tank Gauges

## Oil Level Gauge

Reads the oil level and sends the reading to an indoor receiver. Suitable for use with heating oil and diesel. Fits plastic tanks up to 3m deep. Easy to retrofit. The transmitter needs a 20mm or 32mm hole on top of the tank. No power required at the gauge, has a long-life lithium battery. Comes with an electronic receiver that plugs into a 230V socket. Receiver can be up to 200m away from the tank. Tank level is displayed in ten graduations.



0225

L  
mtrs

£

APOL.1

3

319.60

## Tank Gauge - Float

Suitable for diesel, heating oil, lube oils or water, antifreeze and biodiesel up to B100.

- Gauge provides a simple, rough indication of tank contents
- Shows EMPTY 1/4, 1/2, 3/4 or FULL
- Mounts directly into the top of tank
- Accuracy +/- 5%



0225

L  
mtrs

L  
mtrs

£

FG4E

1.1/2"

1.2

22.65

FG6E

1.1/2"

1.8

26.40

## Tank Gauge - Remote Reading

Simple hydrostatic tank contents gauge. Suitable for use with heating oil and diesel. UNITOP suits tanks from 0.9m to 3.2m high. Probe has 1/2" BSP male tank fitting. Readout can be sited up to 20m away from the tank. Shows percentage of full tank contents. Calibrate on site to suit tank. Pull the plunger and release to show tank contents.



0225

L  
mtrs

£

UNITOP

Rectangular/Cylinder Tanks

310.60

**KELMK**<sup>TM</sup>  
Enhanced Quality Performance

## NYLON TUBING

KELM™ nylon products are produced in a state-of-the-art manufacturing facility. All products undergo rigorous testing to ensure the optimum life can be achieved from the end product. Tube can be produced to your special requirements with optional length, size, colour and branding available (minimum quantities and lead times will apply).

Please contact our Business Development Team for further information.

