

## Press Tools

New generation ultra-compact 32 kN press tool, nearly at the size and weight of a compact tool. Service interval only after 42,000 press cycles!

- Weighs up to 30% less and 15% smaller than our previous unit

### Specifications

- Capacity: 10-108mm
- 270° barrel/jaw swivel
- Hydraulic ram output: 32 kN
- Weight: 3.2kg with battery
- Operating temperature range: +15°F to +122°F (-10°C to +50°C)
- Approximate cycle time: 4 seconds
- LED light for continued operation in no light or low-light environments
- Extremely long service interval – reminder at 40,000, shutdown at 42,000 pressing cycles

- Same functionality and durability of previous models but in a much lighter and more compact design
- Features an LED-light
- Greatly extended service interval of 42,000 cycles
- Standard kit includes: RP 340 press tool, 230V charger, 18V 2.0 A Li-Ion battery and carrying case
- Compatible with all standard series pressing jaws from RIDGID® and other manufacturers
- For use with copper, steel, stainless steel, PEX and multilayer tubing
- For V / TH / U pressfit systems

New generation ultra-compact 32 kN press tool, our lightest corded press tool ever. Service interval only after 42,000 press cycles!

For the peace of mind a corded tool offers, choose the RP 340-C press tool with power adaptor (5m cable). With all of the same features, functionality and durability of the RP 340-B, the RP 340-C press tool is the workhorse of the job site.

- Weighs 23% less than the previous corded unit, RP 340-C is our lightest corded press tool ever
- The corded power adaptor of the RP 340-C can be easily removed and replaced (optionally) by a detachable 18 V Li-Ion battery, offering the user all the advantages of both a corded and battery-powered pressing tool

### Specifications:

- Capacity: 10-108mm
- 270° barrel/jaw swivel
- Hydraulic ram output: 32 kN
- Weight: 3.53 kg with power adaptor
- Cable length: 5m
- Operating temperature range: +15°F to +122°F (-10°C to +50°C)
- Approximate cycle time: 4 seconds
- LED light for continued operations in no light or low-light environments
- Extremely long service interval – reminder at 40,000, shutdown at 42,000 pressing cycles
- For V / TH / U pressfit systems

Press jaws not included



Press jaws not included



### RP340-B

0494	Capacity	kg	⚡	£
43238	10mm - 108mm	8.6	18V	2724.30

### RP340-C

0494	Capacity	kg	⚡	£
43283	10mm - 108mm	8.2	230V	2418.80

- Standard series pressing jaws
- Designed in conjunction with the fitting manufacturer, ensuring compatibility
- Compatible with all RIDGID® standard series pressing tools (RP 300, RP 300-B, RP 330-B, RP 330-C, RP 10-S, RP 340-B and RP 340-C)



### Press Jaws to Suit RP 340-B, V Profile

0494	Capacity	£
83096	12mm	336.80
86256	14mm	336.80
83106	15mm	336.80
86266	16mm	336.80
83116	18mm	336.80
83126	22mm	336.80
83136	28mm	372.70
83146	35mm	372.70
83156	42mm	516.35
83166	54mm	644.45