

# Power Management

## Portable Power Tool Transformers

- Double-wound design for mains isolation
- Insulated splash-proof GRP portable case (IP44)
- 110V centre-tapped to earth (cte) secondary winding to reduce risk of shocks
- 2m input flex

- Input thermal magnetic trip (manual reset) reducing chance of overload
- Manufactured to: BSEN 61558
- Input voltage: 230V AC 1ph
- Output voltage: 110V AC 1ph
- Duty: intermittent

P15/2

- Power: 1500V A
- Sockets: 2 x 16A, 3 pin
- Dimensions: H220 x W180 x D270mm
- Weight: 13kg

P30/2

- Power: 3300V A
- Sockets: 2 x 16A, 3 pin
- Dimensions: H268 x W205 x D227mm
- Weight: 17kg

P50/3

- Power: 5000V A
- Sockets: 2 x 16A, 3 pin and 1 x 32A, 3 pin
- Dimensions: H270 x W310 x D340mm
- Weight: 29kg



110V, with 13A Plug

0712	kVA	Outlet	£
P15/2	1.5	2 x 16 Amp Sockets	90.05
P30/2	3	2 x 16 Amp Sockets	114.10
P50/3	5	1 x 16 & 1 x 32 Amp Sockets	291.60

## Portable Step Up Power Tool Transformers

- GRP portable case with carry handle (IP20)
- Double-wound design for mains isolation
- 230V isolated output
- 2m input flex (1.5mm 3183AG) fitted with moulded 16A 3 pin plug (BSEN 60309)
- Input thermal magnetic trip (manual reset) reducing chance of overload
- Sockets: 16A or 13A, 3 pin (BSEN 60309 / BS1363)
- Manufactured to: BSEN 61558
- Power: 3000V A or 1500V A
- Duty: intermittent
- Input voltage: 110V AC 1ph
- Output voltage: 230V AC 1ph



110V to 240V

0712	kVA	Outlet	£
P24030/13	3	2 x 13 Amp Sockets	164.80
P24030/16	3	2 x 16 Amp Sockets	164.80

## Junction Boxes

- Flexible 4mm yellow cable, 3m length
- Robust plastic case
- Sockets: 2 x 32A, 3 pin (BSEN 60309)
- Carry handle
- Manufactured to: BSEN 61242



110V, Plastic Enclosure, 3 Metre Cable & Plug

0712	Outlet	£
2W32AJBC	32 Amp, 2 Way	83.70

- Robust painted steel case
- Carry handle
- Manufactured to: BSEN 61242

4WJBC  
 • Flexible 1.5mm yellow cable, 5m length  
 • Sockets: 4 x 16A, 3 pin (BSEN 60309)



6WJBC  
 • Flexible 4mm yellow cable, 5m length and 32A 3 pin plug (BSEN 60309)  
 • Sockets: 6 x 16A, 3 pin (BSEN 60309)  
 • 3 x 16A DP output MCB

110V, Steel Enclosure, 5 Metre Cable & Plug

0712	Outlet	Cable Size	£
4WJBC	16 Amp, 4 Way	1.5mm <sup>2</sup>	46.90
6WJBC	16 Amp, 6 Way	4mm <sup>2</sup>	164.80

- Flexible 2.5mm yellow cable, 5m length
- Robust plastic case
- Sockets: 4 x 16A, 3 pin (BSEN 60309)
- Carry handle
- Manufactured to: BSEN 61242



230V, Plastic Enclosure, 5 Metre Cable & Plug

0712	Outlet	£
4WJBC230	16 Amp, 4 Way	44.40

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep, Media, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE