

Hydraulic Hose Range

Page Tech Sheet 5010

Oil Return/Fuel Hose SAE 100R6


100R6 Hose

Application:

- Low pressure hydraulic applications, for use with push style fittings. See page 45

Specification:

- SAE100 R6, exceeds EN854

 Working Temperature:
-40°C to +100°C

Construction:







- Inner tube: oil resistant synthetic rubber (NBR)
- Reinforcement: 1 single textile yarn braid
- Outer cover: oil and weather resistant synthetic rubber

Recommended Fluids:







- Hose suitable for petroleum based hydraulic oil and water-glycol based fluids, air and water

Available per 1mtr







50 Metre Coils, Blue

0303						
100R6-04-B-50	1/4"	13.5	28	65	112	176.40
100R6-06-B-50	3/8"	16.7	28	75	112	277.75
100R6-08-B-50	1/2"	20.6	28	100	112	380.40







25 Metre Coils, Blue

0303						
100R6-12-B-25	3/4"	27.8	21	150	84	285.40
100R6-16-B-25	1"	32.5	20	205	80	371.80

50 Metre Coils, Green

0303						
100R6-04-G-50	1/4"	13.5	28	65	112	176.40
100R6-06-G-50	3/8"	16.7	28	75	112	277.75
100R6-08-G-50	1/2"	20.6	28	100	112	380.40

25 Metre Coils, Green

0303						
100R6-12-G-25	3/4"	27.8	21	150	84	285.40
100R6-16-G-25	1"	32.5	20	205	80	371.80

