

Triple-Lok Tube Fittings



Page Tech Sheet 60429

1. Hydraulics

Male Stud 90° Elbows



BSPT

	0486	OD mm	OD	Wavy	£
4-4C3MXS	6	1/4"	1/4"		17.20
5-4C3MXS	8	5/16"	1/4"		16.90
6C3MXS	10	3/8"	1/4"		17.10
6-6C3MXS	10	3/8"	3/8"		20.45
8C3MXS	12	1/2"	3/8"		21.15
8-8C3MXS	12	1/2"	1/2"		24.80
10-6C3MXS	14,15,16	5/8"	3/8"		25.40
10C3MXS	14,15,16	5/8"	1/2"		26.50
12-8C3MXS	18,20	3/4"	1/2"		47.20
12C3MXS	18,20	3/4"	3/4"		43.75
16-12C3MXS	25	1"	3/4"		61.10
16C3MXS	25	1"	1"		61.00
20-16C3MXS	28,30,32	1.1/4"	1"		93.30
20C3MXS	28,30,32	1.1/4"	1.1/4"		96.40
24C3MXS	35,38	1.1/2"	1.1/2"		117.20



NPT

	0486	OD mm	OD	Wavy	£
4-4CTXS	6	1/4"	1/4"		17.45
5-4CTXS	8	5/16"	1/4"		18.20
6-2CTXS	10	3/8"	1/8"		24.20
6CMTXS	10	3/8"	1/4"		15.80
6-6CMTXS	10	3/8"	3/8"		21.15
8CTXS	12	1/2"	3/8"		20.40
8-8CTXS	12	1/2"	1/2"		24.65
10-6CTXS	14,15,16	5/8"	3/8"		22.95
10CTXS	14,15,16	5/8"	1/2"		30.60
12-8CTXS	18,20	3/4"	1/2"		40.95
12CTXS	18,20	3/4"	3/4"		34.65
12-16CTXS	18,20	3/4"	1"		55.55
16CTXS	25	1"	1"		42.80
20CTXS	28,30,32	1.1/4"	1.1/4"		45.40
24CTXS	35,38	1.1/2"	1.1/2"		50.60



O-Ring Seal (ISO6149), Metric

	0486	OD mm	OD	Wavy	£
4M10C870MXS	6	1/4"	M10x1.0		15.85
5M12C870MXS	8	5/16"	M12x1.5		20.45
6M14C870MXS	10	3/8"	M14x1.5		14.40
6M16C870MXS	10	3/8"	M16x1.5		23.00
8M16C870MXS	12	1/2"	M16x1.5		23.85
8M18C870MXS	12	1/2"	M18x1.5		17.75
12M22C870MXS	18,20	3/4"	M22x1.5		28.10
12M27C870MXS	18,20	3/4"	M27x2.0		40.55
16M33C870MXS	25	1"	M33x2.0		65.20

O-Ring & Retaining Ring (ISO 1179), BSPP

	0486	OD mm	OD	Wavy	£
4C4OMXS	6	1/4"	1/8"		14.20
4-4C4OMXS	6	1/4"	1/4"		13.30
5-4C4OMXS	8	5/16"	1/4"		13.40
6C4OMXS	10	3/8"	1/4"		12.60
6-6C4OMXS	10	3/8"	3/8"		14.75
6-8C4OMXS	10	3/8"	1/2"		22.05
8-4C4OMXS	12	1/2"	1/4"		17.20
8C4OMXS	12	1/2"	3/8"		14.60
8-8C4OMXS	12	1/2"	1/2"		19.25
8-12C4OMXS	12	1/2"	3/4"		34.65
10-6C4OMXS	14,15,16	5/8"	3/8"		19.55
10C4OMXS	14,15,16	5/8"	1/2"		18.85
12-8C4OMXS	18,20	3/4"	1/2"		24.90
12C4OMXS	18,20	3/4"	3/4"		27.50
12-16C4OMXS	18,20	3/4"	1"		40.70
16-12C4OMXS	25	1"	3/4"		41.20
16C4OMXS	25	1"	1"		40.25
20-16C4OMXS	28,30,32	1.1/4"	1"		73.20
20C4OMXS	28,30,32	1.1/4"	1.1/4"		74.50
24C4OMXS	35,38	1.1/2"	1.1/2"		97.10

O-Ring Seal, UNF

	0486	OD mm	OD	Wavy	£
4C5OMXS	6	1/4"	7/16"		17.95
4-6C5OXS	6	1/4"	9/16"		13.85
6C5OMXS	10	3/8"	9/16"		15.15
6-4C5OXS	10	3/8"	7/16"		18.25
6-8C5OXS	10	3/8"	3/4"		26.85
8C5OMXS	12	1/2"	3/4"		20.15
8-10C5OMXS	12	1/2"	7/8"		30.05
10C5OMXS	14,15,16	5/8"	7/8"		28.15
12-10C5OMXS	18,20	3/4"	7/8"		34.15
12C5OMXS	18,20	3/4"	1.1/16"		33.85
12-16C5OXS	18,20	3/4"	1.5/16"		58.95
16C5OMXS	25	1"	1.5/16"		43.70
20C5OXS	28,30,32	1.1/4"	1.5/8"		94.75
24C5OXS	35,38	1.1/2"	1.7/8"		130.50

Male Stud 45° Elbows



BSPT

	0486	OD mm	OD	Wavy	£
4V3MXS	6	1/4"	1/8"		38.90
6V3MXS	10	3/8"	1/4"		29.55
8V3MXS	12	1/2"	3/8"		31.75
12V3MXS	18,20	3/4"	3/4"		38.90
16V3MXS	25	1"	1"		54.65



NPT

	0486	OD mm	OD	Wavy	£
4VTXS	6	1/4"	1/8"		26.10
5VTXS	8	5/16"	1/8"		24.95
6VTXS	10	3/8"	1/4"		30.75
8VTXS	12	1/2"	3/8"		32.90
10VTXS	14,15,16	5/8"	1/2"		36.70
12VTXS	18,20	3/4"	3/4"		42.10
16VTXS	25	1"	1"		62.00



O-Ring & Retaining Ring (ISO 1179), BSPP

	0486	OD mm	OD	Wavy	£
4V4OMXS	6	1/4"	1/8"		25.40
4-4V4OMXS	6	1/4"	1/4"		23.10
6V4OMXS	10	3/8"	1/4"		17.50
6-6V4OMXS	10	3/8"	3/8"		23.80
6-8V4OMXS	10	3/8"	1/2"		29.55
8V4OMXS	12	1/2"	3/8"		22.10
8-8V4OMXS	12	1/2"	1/2"		25.15
10V4OMXS	14,15,16	5/8"	1/2"		20.40
12V4OMXS	18,20	3/4"	3/4"		28.20
16V4OMXS	25	1"	1"		62.05



O-Ring Seal, UNF

	0486	OD mm	OD	Wavy	£
4V5OXS	6	1/4"	7/16"		26.95
6V5OXS	10	3/8"	9/16"		20.60
8V5OXS	12	1/2"	3/4"		21.95
10V5OXS	14,15,16	5/8"	7/8"		28.50
12V5OXS	18,20	3/4"	1.1/16"		50.70
16V5OXS	25	1"	1.5/16"		74.35