

## Swivel Male x Female Stud Couplings



NPT

0486	OD mm	OD	Thread	£
4F6XS	6	1/4"	1/8"	18.80
4-4F6XS	6	1/4"	1/4"	18.40
5F6XS	8	5/16"	1/8"	18.95
6F6XS	10	3/8"	1/4"	18.45
6-6F6XS	10	3/8"	3/8"	20.70
8F6XS	12	1/2"	3/8"	26.10
10F6XS	14,15,16	5/8"	1/2"	28.50
12F6XS	18,20	3/4"	3/4"	28.75
16F6XS	25	1"	1"	40.85



BSPT

0486	OD mm	OD	Thread	£
4F63MXS	6	1/4"	1/8"	19.80
4-4F63MXS	6	1/4"	1/4"	19.80
6F63MXS	10	3/8"	1/4"	21.35
8F63MXS	12	1/2"	3/8"	24.85
10F63MXS	14,15,16	5/8"	1/2"	27.60
12F63MXS	18,20	3/4"	3/4"	32.55
16F63MXS	25	1"	1"	42.20



O-Ring + Retaining Ring (ISO 1179), BSPP

0486	OD mm	OD	Thread	£
4F64OMXS	6	1/4"	1/8"	17.65
5-4F64OMXS	8	5/16"	1/4"	13.10
6F64OMXS	10	3/8"	1/4"	12.60
6-6F64OMXS	10	3/8"	3/8"	14.95
8F64OMXS	12	1/2"	3/8"	14.05
10F64OMXS	14,15,16	5/8"	1/2"	16.25
12F64OMXS	18,20	3/4"	3/4"	20.90
16F64OMXS	25	1"	1"	33.20
20F64OMXS	28,30,32	1.1/4"	1.1/4"	67.75
24F64OMXS	35,38	1.1/2"	1.1/2"	111.05



ED Seal, BSPP

0486	OD mm	OD	Thread	£
4F642EDMXS	6	1/4"	1/8"	16.35
4-4F642EDMXS	6	1/4"	1/4"	12.60
5-4F642EDMXS	8	5/16"	1/4"	13.10
6F642EDMXS	10	3/8"	1/4"	9.70
6-6F642EDMXS	10	3/8"	3/8"	12.70
8-4F642EDMXS	12	1/2"	1/4"	16.25
8F642EDMXS	12	1/2"	3/8"	11.70
8-8F642EDMXS	12	1/2"	1/2"	15.05
10-6F642EDMXS	14,15,16	5/8"	3/8"	15.65
10F642EDMXS	14,15,16	5/8"	1/2"	13.55
12-8F642EDMXS	18,20	3/4"	1/2"	18.45
12F642EDMXS	18,20	3/4"	3/4"	18.95
16-12F642EDMXS	25	1"	3/4"	31.45
16F642EDMXS	25	1"	1"	27.65



O-Ring Seal, UNF

0486	OD mm	OD	Thread	£
4F65OMXS	6	1/4"	7/16"	18.80
6F65OMXS	10	3/8"	9/16"	19.70
8F65OXS	12	1/2"	3/4"	25.50
10F65OXS	14,15,16	5/8"	7/8"	29.40
12F65OMXS	18,20	3/4"	1.1/16"	35.05
16F65OMXS	25	1"	1.5/16"	45.85



O-Ring Seal (ISO6149), Metric

0486	OD mm	OD	Thread	£
4M10F6870MXS	6	1/4"	M10x1.0	21.30
5M12F6870MXS	8	5/16"	M12x1.5	24.20
6M14F6870MXS	10	3/8"	M14x1.5	24.60
8M16F6870MXS	12	1/2"	M16x1.5	29.15
10M18F6870MXS	14,15,16	5/8"	M18x1.5	26.50
12M27F6870MXS	18,20	3/4"	M27x2.0	36.70

## Tube End Reducing Adaptors



Tube x Tube

0486	OD mm	OD	OD mm	OD	£
6-4TRTXS	10	3/8"	6	1/4"	6.70
6-5TRTXS	10	3/8"	8	5/16"	9.10
8-4TRTXS	12	1/2"	6	1/4"	6.80
8-5TRTXS	12	1/2"	8	5/16"	7.35
8-6TRTXS	12	1/2"	10	3/8"	6.20
10-4TRTXS	14,15,16	5/8"	6	1/4"	8.95
10-6TRTXS	14,15,16	5/8"	10	3/8"	8.10
10-8TRTXS	14,15,16	5/8"	6	1/4"	9.70
12-4TRTXS	18,20	3/4"	6	1/4"	12.55
12-6TRTXS	18,20	3/4"	10	3/8"	13.40
12-8TRTXS	18,20	3/4"	12	1/2"	10.35
12-10TRTXS	18,20	3/4"	14,15,16	5/8"	12.40
16-8TRTXS	25	1"	12	1/2"	15.80
16-10TRTXS	25	1"	14,15,16	5/8"	20.55
16-12TRTXS	25	1"	18,20	3/4"	15.80
20-10TRTXS	28,30,32	1.1/4"	14,15,16	5/8"	72.20
20-12TRTXS	28,30,32	1.1/4"	18,20	3/4"	72.20
20-16TRTXS	28,30,32	1.1/4"	25	1"	43.65
24-20TRTXS	35,38	1.1/2"	28,30,32	1.1/4"	54.20

## Gauge Connectors



(ISO 1179-1), BSPP

0486	OD mm	OD	Thread	£
4G4MXS	6	1/4"	1/8"	11.60
4-4G4MXS	6	1/4"	1/4"	14.30
5G4MXS	8	5/16"	1/8"	29.55
6G4MXS	10	3/8"	1/4"	13.55
6-6G4MXS	10	3/8"	3/8"	14.20
8G4MXS	12	1/2"	3/8"	22.50
8-8G4MXS	12	1/2"	1/2"	16.95
10G4MXS	14,15,16	5/8"	1/2"	12.60
12G4MXS	18,20	3/4"	3/4"	34.60
16G4MXS	25	1"	1"	51.55