Hydraulic Quick Release Couplings Pneumatic

Tools.

Page Tech Sheet 20887

These fittings within the industry are known as 10K fitings which have a 10,000 psi working pressure rating. All BSPP fittings are 60° coned for connection to hoses

10,000 psi Rated, 316 Stainless Steel Adaptors

Male x Female Straight Reducers



BSPP

0339	Male 3	Female 3	$[\mathfrak{L}]$
4G-2G-MF-B-10K	1/4"	1/8"	10.80
6G-2G-MF-B-10K	3/8"	1/8"	18.10
6G-4G-MF-B-10K	3/8"	1/4"	18.30
8G-2G-MF-B-10K	1/2"	1/8"	37.45
8G-4G-MF-B-10K	1/2"	1/4"	37.90
8G-6G-MF-B-10K	1/2"	3/8"	38.90
12G-2G-MF-B-10K	3/4"	1/8"	45.30
12G-4G-MF-B-10K	3/4"	1/4"	45.55
12G-6G-MF-B-10K	3/4"	3/8"	46.10
12G-8G-MF-B-10K	3/4"	1/2"	46.40
16G-2G-MF-B-10K	1"	1/8"	81.05
16G-4G-MF-B-10K	1"	1/4"	81.75
16G-6G-MF-B-10K	1"	3/8"	82.15
16G-8G-MF-B-10K	1″	1/2"	82.45
16G-12G-MF-B-10K	1"	3/4"	84.15



NPT

0339	Male \$	Female	\mathfrak{L}
4N-2N-MF-B-10K	1/4"	1/8"	9.45
6N-2N-MF-B-10K	3/8"	1/8"	13.55
6N-4N-MF-B-10K	3/8"	1/4"	13.55
8N-2N-MF-B-10K	1/2"	1/8"	17.85
8N-4N-MF-B-10K	1/2"	1/4"	18.10
8N-6N-MF-B-10K	1/2"	3/8"	18.80
12N-2N-MF-B-10K	3/4"	1/8"	30.35
12N-4N-MF-B-10K	3/4"	1/4"	31.65
12N-6N-MF-B-10K	3/4"	3/8"	32.25
12N-8N-MF-B-10K	3/4"	1/2"	32.25
16N-2N-MF-B-10K	1"	1/8"	53.15
16N-4N-MF-B-10K	1"	1/4"	53.85
16N-6N-MF-B-10K	1″	3/8"	54.85
16N-8N-MF-B-10K	1″	1/2"	57.05
16N-12N-MF-B-10K	1″	3/4"	58.80

Female x Female

Straight **Adaptors**



Swivel, BSPP

0339	\\ \\ \\	{ }	\mathfrak{L}
4G-4G-FF-10K	1/4"	1/4"	23.25
4G-6G-FF-10K	1/4"	3/8"	31.95
4G-8G-FF-10K	1/4"	1/2"	42.20
6G-6G-FF-10K	3/8"	3/8"	29.20
6G-8G-FF-10K	3/8"	1/2"	42.20
8G-8G-FF-10K	1/2"	1/2"	42.75
12G-12G-FF-10K	3/4"	3/4"	46.70
16G-16G-FF-10K	1″	1″	87.40



Fixed, NPT

0339		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	£
2N-2N-FF-10K	1/8"	1/8"	9.45
2N-4N-FF-10K	1/8"	1/4"	12.60
2N-6N-FF-10K	1/8"	3/8"	23.70
2N-8N-FF-10K	1/8"	1/2"	41.80
2N-12N-FF-10K	1/8"	3/4"	59.55
2N-16N-FF-10K	1/8"	1"	92.75
4N-4N-FF-10K	1/4"	1/4"	23.25
4N-6N-FF-10K	1/4"	3/8"	31.85
4N-8N-FF-10K	1/4"	1/2"	42.20
4N-12N-FF-10K	1/4"	3/4"	67.35
4N-16N-FF-10K	1/4"	1"	102.60
6N-6N-FF-10K	3/8"	3/8"	29.10
6N-8N-FF-10K	3/8"	1/2"	42.20
6N-12N-FF-10K	3/8"	3/4"	67.50
6N-16N-FF-10K	3/8"	1"	102.60
8N-8N-FF-10K	1/2"	1/2"	42.75
8N-12N-FF-10K	1/2"	3/4"	76.05
8N-16N-FF-10K	1/2"	1"	113.70
12N-12N-FF-10K	3/4"	3/4"	78.45
12N-16N-FF-10K	3/4"	1"	116.10
16N-16N-FF-10K	1″	1″	128.60



Swivel, JIC

. ,			
0339	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\{\}	£
4J-4J-FF-10K	7/16"	7/16"	40.55
4J-6J-FF-10K	7/16"	9/16"	43.40
4J-8J-FF-10K	9/16"	3/4"	48.70
6J-6J-FF-10K	9/16"	9/16"	46.25
6J-8J-FF-10K	9/16"	3/4"	50.15
8J-8J-FF-10K	3/4"	3/4"	53.35
12J-12J-FF-10K	1.1/16"	1.1/16"	46.70
16J-16J-FF-10K	1.5/16"	1.5/16"	87.40



Maximum Working Pressure: 10,000 psi (690 bar)

Male x Male Elbows



BSPP

0339		\mathfrak{L}
2G-E-MM-10K	1/8"	21.50
4G-E-MM-10K	1/4"	25.95
6G-E-MM-10K	3/8"	34.35
8G-E-MM-10K	1/2"	65.05
12G-E-MM-10K	3/4"	113.20
16G-E-MM-10K	1"	193.55



NPT

0339		£
2N-E-MM-10K	1/8"	52.20
4N-E-MM-10K	1/4"	57.90
6N-E-MM-10K	3/8"	64.30
8N-E-MM-10K	1/2"	58.60
12N-E-MM-10K	3/4"	101.85
16N-E-MM-10K	1"	174.15

