

Spin-on Filter Assemblies

- Disposable spin-on element
- Die-cast aluminium head
- 5 sizes, flows to 200 lpm
- Bypass standard 1 bar (suction 0.2 bar)
- For use with mineral/petroleum based oils

Maximum Working Temperature: +80°C

Maximum Working Pressure: 10 bar



In-line Return, BSPP

	0347		μm		£
SPR08-10-35	1/2"	10	35	27.75	
SPR08-10-70	1/2"	10	70	32.85	
SPR08-10-100	1/2"	10	100	37.50	
SPR08-25-35	1/2"	25	35	27.75	
SPR08-25-70	1/2"	25	70	32.85	
SPR08-25-100	1/2"	25	100	37.50	
SPR12-10-35	3/4"	10	35	27.75	
SPR12-10-70	3/4"	10	70	32.85	
SPR12-10-100	3/4"	10	100	37.50	
SPR12-25-35	3/4"	25	35	27.75	
SPR12-25-70	3/4"	25	70	32.85	
SPR12-25-100	3/4"	25	100	37.50	
SPR16-10-35	1"	10	35	27.75	
SPR16-10-70	1"	10	70	32.85	
SPR16-10-100	1"	10	100	37.50	
SPR16-25-35	1"	25	35	27.75	
SPR16-25-70	1"	25	70	32.85	
SPR16-25-100	1"	25	100	37.50	
SPR20-10-150	1.1/4"	10	150	63.60	
SPR20-10-200	1.1/4"	10	200	72.30	
SPR20-25-150	1.1/4"	25	150	63.60	
SPR20-25-200	1.1/4"	25	200	72.30	

In-line Suction, BSPP

	0347		μm		£
SPS08-10-35	1/2"	10	35	27.75	
SPS08-10-70	1/2"	10	70	32.85	
SPS08-10-100	1/2"	10	100	37.50	
SPS08-25-35	1/2"	25	35	27.75	
SPS08-25-70	1/2"	25	70	32.85	
SPS08-25-100	1/2"	25	100	37.50	
SPS12-10-35	3/4"	10	35	27.75	
SPS12-10-70	3/4"	10	70	32.85	
SPS12-10-100	3/4"	10	100	37.50	
SPS12-25-35	3/4"	25	35	27.75	
SPS12-25-70	3/4"	25	70	32.85	
SPS12-25-100	3/4"	25	100	37.50	
SPS16-10-35	1"	10	35	27.75	
SPS16-10-70	1"	10	70	32.85	
SPS16-10-100	1"	10	100	37.50	
SPS16-25-35	1"	25	35	27.75	
SPS16-25-70	1"	25	70	32.85	
SPS16-25-100	1"	25	100	37.50	
SPS20-10-150	1.1/4"	10	150	63.60	
SPS20-10-200	1.1/4"	10	200	72.30	
SPS20-25-150	1.1/4"	25	150	63.60	
SPS20-25-200	1.1/4"	25	200	72.30	

Return/Suction In-line Spin-on Filter Heads



Working Pressure 10 bar, BSPP Post, BSPP Ports

0347			£
SRFH-08	1/2"	Return	10.80
SSFH-08	1/2"	Suction	10.80
SRFH-12	3/4"	Return	10.80
SSFH-12	3/4"	Suction	10.80
SRFH-16	1"	Return	10.80
SSFH-16	1"	Suction	10.80
SRFH-20	1.1/4"	Return	22.15
SSFH-20	1.1/4"	Suction	22.15

Spin-on Element to Suit S*FH



BSPP

0347	To Suit	μm		£
SE-035-10-12	1/2", 3/4", 1"	10	35	7.75
SE-035-10A-12	1/2", 3/4", 1"	10ABS	35	16.50
SE-035-25-12	1/2", 3/4", 1"	25	35	7.75
SE-070-10-12	1/2", 3/4", 1"	10	70	12.85
SE-070-10A-12	1/2", 3/4", 1"	10ABS	70	27.00
SE-070-25-12	1/2", 3/4", 1"	25	70	12.85
SE-100-10-12	1/2", 3/4", 1"	10	100	17.65
SE-100-10A-12	1/2", 3/4", 1"	10ABS	100	37.30
SE-100-25-12	1/2", 3/4", 1"	25	100	17.65
SE-150-10-20	1.1/4"	10	150	32.35
SE-150-25-20	1.1/4"	25	150	32.35
SE-200-10-20	1.1/4"	10	200	41.05
SE-200-25-20	1.1/4"	25	200	41.05

Visual Indicator



Return, NPT

0347		£
VRG	1/8"	9.15

Suction, NPT

0347		£
VSG	1/8"	9.15

For...



Oil/Fluid Drain Pan



...see page 1698

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep, Media, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE