

## Gauge Isolator Valves

Designed to prevent pressure gauge damage and extend gauge life. The gauge isolator valve when installed between gauge and pressure line protects the pressure gauge from continuous hydraulic pressure, surges or shock loads.


Single Station:

Cast iron and steel. Knurled aluminium knob twist to lock or push to read type.

Maximum W/P:  
350 bar

Port Size:  
Single station = G1/4

Weight:  
Single station = 0.90kg



Single Station

0045		Element Media	£
GI1414	Push to Read	1/4"	104.15

## Modular Filler Breathers

Construction:

Moulded in non-corrodible glass-filled nylon combining strength with lightweight design.

Options:

- Single 63mm diameter hole filler breather installation that eliminates drilled and tapped holes using self-locking clamps
- 6 Hole Filler breather installation that uses 6 x No. 10 thread forming screws
- 3 Hole Filler breather installation that uses 3 x No. 10 thread forming screws

Filtration: Expanded polyurethane foam, 10 micron.

Seals: Nitrile.



Tech Sheet  
636

Un-pressurised, 10 Micron

0045		£
AB98210011UC	Single Hole	26.00
AB98810011UC	6 Hole	27.65
AB68118	3 Hole	32.40

## Screw-on Type Air Breather (IP65)

Manufactured from non-corrodible glass filled nylon.



Tech Sheet  
636

Un-pressurised 10 Micron, BSPP,  
101mm Diameter

0045		£
AB98410101UC	3/4"	17.55

Manufactured from in glass filled nylon and glass-coupled polypropylene.

Un-pressurised 10 Micron, BSPP,  
70mm Diameter

0045		£
SAB6101	G1/2	25.20
SAB7101	G3/4	25.20

## Suction Strainers

Construction:

- Stainless steel media 30% glass-filled nylon head
- Zintec centre tube and end cap
- Epoxy adhesives

Filter Media: 125 micron.

Flow Range: 15-500 l/min.

Mounting Threads: G1/2 up to G3

Maximum Working Temperature:  
+90°C

Tech Sheet  
60433



BSPP, Without Bypass

0045	Old Ref.			£
SE1319	SS1A1S1AP	1/2"	15	24.45
SE1320	SS1B2A1AP	3/4"	25	32.40
SE1457	SS1B3A1AP	1"	50	34.50
SE1323	SS1C4A1AP	1.1/2"	95	44.25
SE1324	SS1C5A1AP	1.1/2"	130	55.10
SE1326	SS1C6A1AP	2"	180	71.05
SE1219	SS1D7A1AP	2"	225	119.45
SE1220	SS1D8A1AP	2.1/2"	350	138.25
SE1221	SS1D9A1AP	3"	500	173.85

BSPP, With Bypass

0045			£
SE5100	1/2"	15	28.40
SE5101	3/4"	25	35.30
SE5102	1"	50	41.30
SE5103	1.1/2"	95	48.20
SE5104	1.1/2"	130	53.90
SE5105	2"	180	68.35
SE5106	2"	225	121.00
SE5107	2.1/2"	350	138.60
SE5108	3"	500	164.75

For...



Triple-Lok  
Tube Fittings



...see pages 246-251