Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep., Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main

Adaptors & Fittings

Stainless Steel

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives Blow Guns Vacuum & Nozzles

# Page Tech Sheet 60403



Maximum Working Pressure:

# **Pumps**

- · Metal reservoirs resist cracking
- Built-in bypass device protects the hydraulic system from over-pumping damage (US Patent No. 5,946,912)
- Compact yet powerful air turbo motor (US Patent No. 5,341,723)
- Suggested air inlet range: 110-175 psi (7.6-12.1 bar)



### Air Pump, Single Acting



- · Portable, lightweight and compact design
- · Universal motor starts under full load
- · 3m 24V AC pendant control for safety
- · Weighs only 17kg with oil
- External pressure adjustment is available
- · Designed for intermittent duty operation
- · Gauge port on control valve



## Universal Motor Pump

0481	<b>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</b>
PU20M4N01B	3/8"









Tech Sheet

60406

#### · Metal reservoirs resist cracking

- · Internal pressure relief valve for overload protection
- Perfect for use with cylinders and hydraulic tools or OEM applications
- Two-speed pumps reduce user fatigue and increase productivity



## Single Speed Hand Pump, Single Acting





#### Two-speed Hand Pumps, Single Acting

0481		Oil Capacit y cm³	Material	$\mathfrak{L}$
P350	3/8"	350	Aluminium	493.90
P1000	3/8"	1000	Aluminium	582.10



### Hand Pump, Double Acting

	-
0481	<b>\{</b>



Steel

1278.80

Pressure Wash, Fuelling & Lubrication Air Tools & Compresso Equipment

Tools.

