

# Hydraulic Couplings



## Tech Sheet 2128

Only plug and socket with same thread fit together.

Ideal for hydraulic dump trucks, oil field equipment, spreading equipment and applications requiring the ability to connect or disconnect under pressure.  
With Standard Seals: Nitrile

Working Temperature:  
-25°C to +120°C

### Screw-on Couplings, 98 Series



Brass Body/Zinc Plated Steel Wing Nut.



Wing Nut, NPTF

Plug, NPTF

8111			£
HFBFC9834	3/4"	210	72.35
HFBFC9810	1"	210	92.15
HFBFC98114	1.1/4"	190	162.35
HFBFC98112	1.1/2"	175	175.60

8111			£
HFBFP9834	3/4"	210	52.90
HFBFP9810	1"	210	58.95
HFBFP98114	1.1/4"	190	120.70
HFBFP98112	1.1/2"	175	146.90

# High Pressure Spin-on Couplings (Carbon Steel)



## Tech Sheet 10005

### 88 Series

Interchangeability:  
Hansen HP3 Series  
Parker 3000 Series  
Faster PVVM Series

DNP PVS Series  
Stucchi IVHP Series  
Safeway S30 Series

This series of couplings with their threaded union locking system and precision ball-type check valves, are designed for extreme high pressure applications such as found on portable hydraulic rams.

Working Temperature:  
-25°C to +120°C

Maximum Working Pressure:  
700 bar



Coupling with Nitrile Seals, NPTF

8111		£
HFSFC8814	1/4"	26.10
HFSFC8838	3/8"	26.30



88 Series Aluminium Dust Covers

8111	To Suit	£
HFSFC-14-DP	1/4"	6.05
HFSFC-38-DP	3/8"	6.25
HFSFP-14-DC	1/4"	7.65
HFSFP-38-DC	3/8"	8.50



Plug with Nitrile Seals, NPT

8111		£
HFSFP8814	1/4"	15.90
HFSFP8838	3/8"	16.25

2. Hydraulic Quick Release Couplings

Hydraulics  
Hydraulic Quick Release Couplings  
Pneumatic Quick Release Couplings  
Air Prep, Media, Monitor & Test  
KELM™ Pneumatics

Pneumatic & Vacuum Equipment  
Valves  
Ring Main Systems  
Adaptors & Fittings  
Stainless Steel  
Malleable Iron  
Hose, Tubing & Couplings  
Clamps & Clips  
Sprays & Adhesives  
Blow Guns, Vacuum & Nozzles  
Pressure Wash, Fuelling & Lubrication  
Air Tools & Compressor Equipment  
Tools, Hardware & PPE