# Hydraulic Quick Release Couplings



## PCJ5 Series, Ultra High Pressure Couplings

DNP standard, interchange with CEJN 115 series, 15,000 psi/1,000 bar working pressure, high resistance steel, locking radial balls. Tested 100% with helium at low and high pressure. PCJ5 series series is ideal for high pressure tools and torque equipment.

Interchangeability: Cejn 115 Occlusion: poppet Locking: radial balls

Material: high resistance steel Finishing: Zn-Fe (Cr III) Available Threads: BSP, NPT

Standard Seals: special compound Safety Factor: 1:2,5 Test: with helium, 100% at low and high pressure

Connection Under Pressure:

not allowed

Tech Sheet 20488



Working

Temperature:

Maximum Working Pressure: 1000 bar



### Plug for Coupling

PCJ5 Protection

0457 SPCJ.06002

To Suit ISO 6.3 Material PVC

2.45



#### Coupling, BSPP

0457	<b>\{\}</b>	ISO	bar	£
PCJ5.0604.002	1/8"	6.3	1000	120.90
PCJ5.0606.002	1/4"	6.3	1000	120.90
PCJ5.0610.002	3/8"	6.3	1000	125.15

Coupling, NPT	-			
0457	<b>{ }</b>	Iso	bar	£
PCJ5.0606.012	1/4"	6.3	1000	120.90
PCJ5.0610.012	3/8"	6.3	1000	125.15

### Plug, BSPP

0457		ISO	bar	$[\mathfrak{L}]$
PCJ5.0604.003	1/8"	6.3	1000	45.90
PCJ5.0606.003	1/4"	6.3	1000	45.90
PCJ5.0610.003	3/8"	6.3	1000	50.10

#### Plua, NPT

0457		Iso	bar	£
PCJ5.0606.013	1/4"	6.3	1000	45.90
PCJ5.0610.013	3/8"	6.3	1000	50.10





To Suit ISO 6.3

To Suit

ISO 6.3

To Suit

ISO 6.3

Material

PVC

Material

**PCJ6 Protection** 

Caps & Plugs

Plug for Coupling

0457

SPCJ.06042

Cap For Plug

0457

SPCJ.06043

Material PVC

Air Prep., Media, Monito & Test  $\overline{\mathfrak{L}}$ KELM™

2 45

Pneumatics

Pneumatic & Vacuum Equipment

Valves

Systems

Adaptors & Fittings

Stainless

3

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools.

## PCJ6 Series, Ultra High Pressure Couplings

DNP standard, interchange with CEJN 116 series, 21,780 psi/1,500 bar working pressure, high resistance steel, locking radial balls. Tested 100% with helium at low and high pressure. PCJ6 series is ideal for high pressure tools and torque equipment.

Interchangeability : Cejn 116 Occlusion: poppet Locking: radial balls Material: high resistance steel

Finishing: Zn-Fe (Cr III) Available Threads: BSP, NPT Standard Seals: special compound Safety Factor: 1:2,5 Test: with helium, 100% at low

and high pressure Connection Under Pressure: not allowed



Maximum Working Pressure: 1500 bar

Working

Temperature:

-35°C to +130°C

20489



#### Coupling, BSPP

0457	<b>{ { {</b>	ISO	bar	£
PCJ6.0606.002	1/4"	6.3	1500	141.85

#### Coupling, NPT

1 3,	
0457	<b>{ }</b>
PCJ6.0606.012	1/4"

1/4" 6.3











Plug, NPT

PCJ6.0606.013

0457





bar

1500



£

66.80

ISO

