


075 Series

kee


Tech Sheet 60436

 Working Temperature:
-20°C to +100°C
EPDM & Viton available on request

 Maximum Working Pressure:
35 bar

Back body:
Brass (MS 58) nickel plated.
Valve body:
Brass (MS 58) nickel plated.
Sleeve: Steel nickel plated.
Spring and locking ring:
Stainless steel 301.
Locking balls: Stainless steel 301.
Seals: NBR .

Plug body: Steel nickel plated.
Interchangeability:
Interchangeable with the Rectus 25 series and Cejn 320 NW 7.8.
Application:
075 series is specially suited to compressed air applications. Its compact dimensions and single-handed operation make it suitable for numerous applications.





Actual Size

Couplings





Male Thread, BSPT

| 0492 |  |  | £ |
|--------------|---|---|-------|
| 075CVMT14SNN | 1/4" | 60 | 23.05 |
| 075CVMT38SNN | 3/8" | 60 | 20.90 |
| 075CVMT12SNN | 1/2" | 55 | 25.05 |




Female Thread, BSPP

| 0492 |  |  | £ |
|--------------|---|---|-------|
| 075CVFP14SNN | 1/4" | 55 | 20.90 |
| 075CVFP38SNN | 3/8" | 55 | 21.25 |
| 075CVFP12SNN | 1/2" | 56 | 24.75 |





Hose Tail

| 0492 | To Suit Hose I.D. |  | £ |
|--------------|-------------------|---|-------|
| 075CVHT06SNN | 6mm (1/4") | 71 | 20.90 |
| 075CVHT08SNN | 8mm (5/16") | 71 | 20.90 |
| 075CVHT10SNN | 10mm (3/8") | 71 | 21.20 |
| 075CVHT13SNN | 13mm (1/2") | 71 | 21.90 |

Plugs





Male Thread, BSPT

| 0492 |  |  | £ |
|--------------|---|---|-------|
| 075PNMT14SXN | 1/4" | 37 | 4.80 |
| 075PNMT38SXN | 3/8" | 37 | 5.75 |
| 075PNMT12SXN | 1/2" | 42 | 11.25 |




Female Thread, BSPP

| 0492 |  |  | £ |
|--------------|---|---|-------|
| 075PNFP14SXN | 1/4" | 37 | 5.05 |
| 075PNFP38SXN | 3/8" | 37 | 5.80 |
| 075PNFP12SXN | 1/2" | 37 | 11.25 |



Hose Tail

| 0492 | To Suit Hose I.D. |  | £ |
|--------------|-------------------|---|------|
| 075PNHT06SXN | 6mm (1/4") | 46 | 4.80 |
| 075PNHT08SXN | 8mm (5/16") | 46 | 4.80 |
| 075PNHT10SXN | 10mm (3/8") | 48 | 4.80 |
| 075PNHT13SXN | 13mm (1/2") | 48 | 8.15 |