

Series 19KA & Accessories



Y Connector



2 x Coupling Outlets, 1 x Plug Inlet

| | | |
|------|-----|-------|
| 1910 | | £ |
| 19Y | 117 | 39.65 |

Triple Outlet Connectors



3 x Coupling Outlets, 1 x 3/8" BSPP Inlet

| | | |
|------|-----|-------|
| 1910 | | £ |
| 19W | 111 | 90.40 |



3 x Coupling Outlets, 1 x 1/4" BSPP Inlet

| | | |
|-------|--|-------|
| 1910 | | £ |
| M3-19 | | 55.60 |

Free Angle Rotating Joint



Male, BSPT

| | | |
|----------|------|-------|
| 1910 | | £ |
| 19FAAK13 | 1/4" | 33.05 |
| 19FAAK17 | 3/8" | 33.05 |
| 19FAAK21 | 1/2" | 41.30 |



Female, BSPP

| | | |
|----------|------|-------|
| 1910 | | £ |
| 19FAIW13 | 1/4" | 33.05 |

Leader Hoses

Tech Sheet 1337



3/8" Bore Rubber-Tech Hose, Plug One End x Male Thread, BSPT

| | | | |
|----------|------|-----|-------|
| 1910 | | | £ |
| LH19/13K | 1/4" | 381 | 18.40 |
| LH19/17K | 3/8" | 381 | 20.55 |
| LH19/21K | 1/2" | 381 | 20.95 |

A 'Leader Hose' is a length of flexible hose which should be fitted between an air tool & the connecting coupling.

By absorbing the impact of a pneumatic impact tool, a leader hose will significantly increase the life expectancy of the coupling.

WARNING – Leader Hoses



The Health & Safety Executive guide states - "the plug should not be screwed directly into the inlet port, but should be fitted onto a short isolation hose, thus isolating the plug & coupling from the tool vibration".

You might also need...

Tyre Inflators



...on pages 1722-1724

Other materials, seals and finishes available on request, please contact our technical department for further details.