

Series 21KB



Page Tech Sheet 509

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Actual Size

Flow Rate: 560 L/Min
Material: Brass, Buna seal (standard series coupling)
Application: General purpose pneumatic coupling, medical, dental, robotics, instrumentation

Couplings



Male Thread, BSPP

2110				
21KBAW10MPX	1/8"	14	36	23.70
21KBAW13MPX	1/4"	17	38	23.70



Plastic Hose Connection

2110	To Fit Tube Size mm			
21KBK006MPX	6 x 4	14	42	27.90
21KBK008MPX	8 x 6	14	42	27.90



Female Thread, BSPP

2110				
21KBIW10MPX	1/8"	14	36	23.70
21KBIW13MPX	1/4"	17	38	23.70



Hose Tail

2110	To Suit Hose I.D.			
21KBTf04MPX	4mm (1/8")	14	46	25.85
21KBTf06MPX	6mm (1/4")	14	46	25.85
21KBTf08MPX	8mm (5/16")	14	46	26.40

Plugs



Male Thread, BSPP

2110				
21SBAW10MPX	1/8"	14	40	18.20
21SBAW13MPX	1/4"	17	42	18.55



Female Thread, BSPP

2110				
21SBIW10MPX	1/8"	14	40	18.20
21SBIW13MPX	1/4"	17	42	18.55



Hose Tail

2110	To Suit Hose I.D.			
21SBTF06MPX	6mm (1/4")	14	50	22.85
21SBTF08MPX	8mm (5/16")	14	50	23.70



Plastic Hose Connection

2110	To Fit Tube Size mm			
21SBK006MPX	6 x 4	14	46	23.60
21SBK008MPX	8 x 6	14	46	23.60

Other materials, seals and finishes available on request, please contact our technical department for further details.